NERI

Project location:	Fixture type: Qty:
Project name:	Notes:

KUMA | POLE | CAST IRON + STEEL | SIMPLE | MAX 2 LIGHT SOURCES



CE

ORDERING INFORMATION / GUIDE

Example**: KU1300000-N-BM-EPR-GA2-HC0370-ZD152089-CN0**

GROUND FIXING	SHAPE	TOP SET UP / LIGHT POINTS	HEIGHT	SECTION	FINISH
BM Buried root	**EPR** Tapered	**GA1** Bracket | Suspended swan neck | Max 1 light source	**HC0370** 3700 mm	**ZD152089** Base 152 - Top 89 mm	**CN0** Grey [Neri] Textured
BF Flanged		**GA2** Bracket | Suspended swan neck | Max 2 light sources	**HC0470** 4700 mm		

Generated code: **KU1300000 - N** - _ _ - _ _ _ - _ _ _ - _ _ _ _ _ _ _ - _ _ _ _ _ _ _ _ _ - _ _ _

ON REQUEST
Non-standard variants and configurations available upon request. Please contact Neri for further information.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

KUMA | POLE | CAST IRON + STEEL | SIMPLE | MAX 2 LIGHT SOURCES

MECHANICAL CHARACTERISTICS

Pole in cast iron UNI EN 1561 and steel UNI EN 10219-1, hot-dip galvanized according to UNI EN ISO 1461.
CE-certified pole, compliant with standard UNI EN 40-5.

Section: Base/Top 152/89 mm
Hatch size: 186x45 mm
Height under ground: 600 mm
Slot height below ground line for cable entry: 150x50 mm
Weight: 80-91 kg
Finish: Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.