
NERI

Project location:		Fixture type:	Qty:
Project name:		Notes:	

KAUS PROJECTOR | LUMINAIRE | KAUS PROJECTOR L





CE IP66 IK08 Classe II

ORDERING INFORMATION / GUIDE

Example**: LUKAU02-N-D76-827-L017-ST-V1-F27-M2-CN0**

OPTIQUE	RA+K	LUMINOUS FLUX	SCREEN FINISH	POWER SUPPLY	DRIVER FUNCTION	ISO CLASS	FINISH
D76 Spot	**827** Ra80 2700 K	**L017** 1700 lm	**ST** Transparent	**V5** 24V	**F52** PWM	**M2** Class II	**CN0** Grey [Neri] Textured
D77 Flood	**830** Ra80 3000 K			**V1** 220V-240V	**F27** ON/OFF+CLO	**M3** Class III	
D78 Flood	**840** Ra80 4000 K						

Generated code: **LUKAU02 - N** - _ _ _ - _ _ _ - _ _ _ _ - _ _ - _ _ - _ _ _ - _ _ - _ _ _

CONFIGURATION NOTES
The product features shown in this datasheet cannot always be freely combined.
To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

ON REQUEST
Non-standard variants and configurations available upon request. Please contact Neri for further information.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

KAUS PROJECTOR | LUMINAIRE | KAUS PROJECTOR L

SOURCE
COB LED.

Energy-efficiency class: D
LED forward current: 380 mA
Power rating: 13.7 W
Nominal Flux: 1689 lm
Nominal CCT (Colour temperature): 2700 K, 3000 K, 4000 K
Color Rendering Index (Ra): 80
Standard Deviation Colour Matching: ≤3
ANSI/IES TM-30: Rf = 84 Rg = 97
Rated lifetime: L80B50 60000 h @ Tq = 25 °C

LIGHTING CHARACTERISTICS
TIR lens in PMMA.

Optique: Spot, Flood
Optical efficiency: LOR = 100% ULOR = 0%
LED quantity: 1
Cutoff Angle: Cutoff C = 0° γ = 0°
Luminous flux: 1689 lm
Luminous efficacy: 105 lm/W
IPEA: Road A3+ / A3+, Urban A3+ / A3+, Ped A++ / A++, Park A++ / A++, Art A6+ / A6+
BUG: B=2, U=0-1, G=0
Photobiological safety: RG1 - Low risk

ELECTRICAL CHARACTERISTICS
Compliant with standards EN 60598-1; EN 60598-2-3; EN 62031; EN 55015 EMC; EN 61547 EMC; EN 61000-3-2/3; IEC/TR 62778.

Luminaire power: 16.1 W
Power supply: 220V-240V~ 50/60Hz, 24V
Power factor: ≥0.9
Insulation class: Class II, Class III
Control type - driver: PWM, ON/OFF+CLO
Safe Flicker: PstLM=<1 e SVM=<0,4 (IEC TR 61547-1 e IEC TR 63158)
Ambient temperature: -40 °C / +50 °C
Driver included: Yes
Cable type: H05RN-F 2X1mm²
Cable length: 2 m
Surge protection: 2kV CM - 2kV DM

MECHANICAL CHARACTERISTICS
Structure composed of a die-cast aluminum base and body (UNI EN 1706), with a transparent tempered flat glass protective screen, IK08 impact resistant (EN 62262).
±90° tilt adjustment system with 30° steps.
Gasket with closure via shaped tool and high thermal conductivity aluminum PCB (≥ 2.0 W/mK).
Stainless steel screws; fixing plugs not included.

Length: 135 mm
Width: 75 mm
Height: 122 mm
Weight: 1 kg
Protection degree: IP66
Mechanical resistance: IK08
Finish: Grey [Neri] Textured

INSTALLATION
Installation via anchors fastening (not included).
Adjustable ±90° with 30° steps.
Anchors not included.
Adjustable ±90° in 30° increments.


WARNINGS
Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional.
Replaceable control gear by a professional.
Protection of surfaces: please refer to the specification on painting procedures of the materials.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

KAUS PROJECTOR | LUMINAIRE | KAUS PROJECTOR L

Optic: Spot


Screen finish: Transparent



H [m]	D [m]	Emax [lx]
	17	
1	0.3	7824
2	0.6	1956
3	0.9	869
4	1.2	489
5	1.49	313

Optic: Flood


Screen finish: Transparent



H [m]	D [m]	Emax [lx]
	27	
1	0.48	3730
2	0.96	933
3	1.44	414
4	1.92	233
5	2.4	149

Optic: Flood

Screen finish: Transparent



H [m]	D [m]	Emax [lx]
	39	
1	0.71	2146
2	1.42	537
3	2.12	238
4	2.83	134
5	3.54	86

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

KAUS PROJECTOR | LUMINAIRE | KAUS PROJECTOR L

Optic: Spot

Screen finish: Transparent

System					Source			IPEA				
Luminous Flux	**Nominal CCT**	**W**	**lm/W**	**n° led**	**mA**	**W**	**lm/W**	**Road**	**Urban**	**Ped**	**Park**	**Art**
1689 lm	2700 K	16.1	105	1	380	13.7	123	A3+	A3+	A++	A++	A6+
1689 lm	3000 K	16.1	105	1	380	13.7	123	A3+	A3+	A++	A++	A6+
1689 lm	4000 K	16.1	105	1	380	13.7	123	A3+	A3+	A++	A++	A6+

Optic: Flood

Screen finish: Transparent

System					Source			IPEA				
Luminous Flux	**Nominal CCT**	**W**	**lm/W**	**n° led**	**mA**	**W**	**lm/W**	**Road**	**Urban**	**Ped**	**Park**	**Art**
1689 lm	2700 K	16.1	105	1	380	13.7	123	A3+	A3+	A++	A++	A6+
1689 lm	3000 K	16.1	105	1	380	13.7	123	A3+	A3+	A++	A++	A6+
1689 lm	4000 K	16.1	105	1	380	13.7	123	A3+	A3+	A++	A++	A6+

Optic: Flood

Screen finish: Transparent

System					Source			IPEA				
Luminous Flux	**Nominal CCT**	**W**	**lm/W**	**n° led**	**mA**	**W**	**lm/W**	**Road**	**Urban**	**Ped**	**Park**	**Art**
1689 lm	2700 K	16.1	105	1	380	13.7	123	A3+	A3+	A++	A++	A6+
1689 lm	3000 K	16.1	105	1	380	13.7	123	A3+	A3+	A++	A++	A6+
1689 lm	4000 K	16.1	105	1	380	13.7	123	A3+	A3+	A++	A++	A6+

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.