

Example: **NORTSB-U-BF-EPF-GX2-HC0396-ZD102102-CN0**

Ground fixing	Shape	Top Set up / Light points	Height	Section	Finish
BF Flanged	EPF Cylindrical	GX1 Max 1 light source	HC0396 155.984 in	ZD102102 Base 4.016 - Top 4.016 in	CN0 Grey [Neri] Textured
		GX2 Max 2 light sources	HC0488 192.008 in	ZD114114 Base 4.488 - Top 4.488 in	
		HC0579 227.992 in			

Generated code: **NORTSB - U** - - - - -

CONFIGURATION NOTES

CONFIGURATION NOTES
The product features shown in this datasheet cannot always be freely combined.

To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

Nova | Pole | Aluminum | Round straight | Max 2 light sources

MECHANICAL CHARACTERISTICS

Circular-section aluminum lighting pole made of 6061-T6 aluminum (ASTM B221-20) and 356-T6 aluminum casting, complete with horizontal top arm for side-mounted fixture with plastic terminal, inspection door, base flange and hot-dip galvanized steel anchor bolts (ASTM F1554-55).

Section	Base/Top 4.016/4.016 in, 4.488/4.488 in
Hatch size	2x4 in
Slot height below ground line for cable entry	2x4 in
Weight	42-78.99 lb
Finish	Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.