
NERI

Project location:	Fixture type: Qty:
Project name:	Notes:

KAUS BOLLARD | LUMINAIRE | KAUS BOLLARD 360°





CE IP65 IK07

ORDERING INFORMATION / GUIDE

Example**: BOKAU01-N-D52-830-L003-ST-V1-F06-M1-CN0**

OPTIQUE	RA+K	LUMINOUS FLUX	SCREEN FINISH	POWER SUPPLY	DRIVER FUNCTION	ISO CLASS	FINISH
D52 360°	**830** Ra80 3000 K	**L003** 300 lm	**ST** Transparent	**V1** 220V-240V	**F06** DALI+CLO	**M1** Class I	**CN0** Grey [Neri] Textured

Generated code: **BOKAU01 - N** - _ _ _ - _ _ _ - _ _ _ _ - _ _ - _ _ - _ _ _ - _ _ - _ _ _

ON REQUEST
Non-standard variants and configurations available upon request. Please contact Neri for further information.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

KAUS BOLLARD | LUMINAIRE | KAUS BOLLARD 360°

Compact design engineered to ensure long-term durability and reliability.

SOURCE

LED 3030 MID-Power.

Energy-efficiency class: D
LED forward current: 89 mA
Power rating: 6.4 W
Nominal Flux: 276 lm
Nominal CCT (Colour temperature): 3000 K
Color Rendering Index (Ra): 80
Standard Deviation Colour Matching: ≤3
ANSI/IES TM-30: Rf = 84 Rg = 97
Rated lifetime: L80B50 30000 h @ Tq = 25 °C

LIGHTING CHARACTERISTICS

Internal aluminum reflector.

Optique: 360°
Optical efficiency: LOR = 100% ULOR = 15%
LED quantity: 24
Cutoff Angle: Semi Cutoff C = 0° γ = 37°
Luminous flux: 276 lm
Luminous efficacy: 37 lm/W
Maximum luminous intensity γ 90°: ≤29.04 cd/klm
Luminous intensity class: G*2
IPEA: Road F / F, Urban F / F, Ped F / F, Park F / F, Art F / F
BUG: B=0, U=2, G=0
Photobiological safety: RG1 - Low risk

ELECTRICAL CHARACTERISTICS

Compliant with standards EN 60598-1; EN 60598-2-3; EN 62031; EN 55015 EMC; EN 61547 EMC; EN 61000-3-2/3; IEC/TR 62778.

Luminaire power: 7.5 W
Power supply: 220V-240V~ 50/60Hz
Power factor: ≥0.9
Insulation class: Class I
Control type - driver: DALI+CLO
Safe Flicker: PstLM=<1 e SVM=<0,4 (IEC TR 61547-1 e IEC TR 63158)
Ambient temperature: -40 °C / +50 °C
Driver included: Yes
Cable type: H07RN-F 5G1mm²
Cable length: 0.5 m
Surge protection: 2kV CM - 2kV DM

MECHANICAL CHARACTERISTICS

Extruded aluminum structure with integrated die-cast aluminum heat sink.
Protective screen in transparent PMMA and high-resistance plastic components.

Diameter: 100 mm
Height: 800 mm
Weight: 4.4 kg
Wind-exposed area: 0.09 m²
Protection degree: IP65
Mechanical resistance: IK07
Finish: Grey [Neri] Textured

INSTALLATION

Installation via anchors fastening (not included).
Anchors not included.

WARNINGS


Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional.
Replaceable control gear by a professional.
Protection of surfaces: please refer to the specification on painting procedures of the materials.


Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

KAUS BOLLARD | LUMINAIRE | KAUS BOLLARD 360°

Optic: 360°

Screen finish: Transparent





Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

KAUS BOLLARD | LUMINAIRE | KAUS BOLLARD 360°

Optic: 360°

Screen finish: Transparent

System					Source			IPEA				
Luminous Flux	**Nominal CCT**	**W**	**lm/W**	**n° led**	**mA**	**W**	**lm/W**	**Road**	**Urban**	**Ped**	**Park**	**Art**
276 lm	3000 K	7.5	37	24	89	6.4	43	F	F	F	F	F

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.