

Matar | Pole | Steel + Aluminium | Round step | Max 2 light sources



Ordering Information / Guide

Example: **MA1113000-N-BF-EPR-GD2-HC0500-ZD140089-CNO**

Ground fixing	Shape	Top Set up / Light points	Height	Section	Finish
BF Flanged	EPR Tapered	GD2 Suspended bracket Max 2 light sources	HC0500 196.851 in	ZD140089 Base 5.512 - Top 3.504 in	CNO Grey [Neri] Textured
			HC0600 236.221 in	ZD159089 Base 6.26 - Top 3.504 in	
			HC0700 275.591 in	ZD168089 Base 6.614 - Top 3.504 in	
			HC0800 314.961 in		
			HC0900 354.331 in		
			HC1000 393.701 in		

Generated code: **MA1113000 - N** - _ _ - _ _ - _ _ _ _ - _ _ _ _ _ - _ _ _

CONFIGURATION NOTES
The product features shown in this datasheet cannot always be freely combined.
To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

Matar | Pole | Steel + Aluminium | Round step | Max 2 light sources**MECHANICAL CHARACTERISTICS**

Pole in steel UNI EN 10219 and aluminum casting EN 1706 AC-46100KF, hot-dip galvanized according to UNI EN ISO 1461.

CE-certified pole, compliant with standard UNI EN 40-5.

Section	Base/Top 5.512/3.504 in, 6.26/3.504 in, 6.614/3.504 in
Hatch size	7.323x1.772 in
Height under ground	3.937 in
Weight	114.64-315.26 lb
Finish	Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.