NERI

Project location:	Fixture type: Qty:
Project name:	Notes:

MIZAR | POLE | CAST IRON + STEEL | CONICAL | MAX 2 LIGHT SOURCES



CE

ORDERING INFORMATION / GUIDE

Example**: MZ1410000-N-BM-EPR-GA2-HC0380-ZD127102-CN0**

GROUND FIXING	SHAPE	TOP SET UP / LIGHT POINTS	HEIGHT	SECTION	FINISH
BM Buried root	**EPR** Tapered	**GA1** Bracket | Suspended swan neck | Max 1 light source	**HC0380** 3800 mm	**ZD127102** Base 127 - Top 102 mm	**CN0** Grey [Neri] Textured
BF Flanged		**GA2** Bracket | Suspended swan neck | Max 2 light sources	**HC0480** 4800 mm		

Generated code: **MZ1410000 - N** - _ _ - _ _ _ - _ _ _ - _ _ _ _ _ _ - _ _ _ _ _ _ _ _ - _ _ _

CONFIGURATION NOTES
The product features shown in this datasheet cannot always be freely combined.
To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

ON REQUEST
Non-standard variants and configurations available upon request. Please contact Neri for further information.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

MIZAR | POLE | CAST IRON + STEEL | CONICAL | MAX 2 LIGHT SOURCES

MECHANICAL CHARACTERISTICS

Pole in steel UNI EN 10219 and cast iron UNI EN 1561, hot-dip galvanized according to UNI EN ISO 1461.
CE-certified pole, compliant with standard UNI EN 40-5.

Section: Base/Top 127/102 mm
Hatch size: 186x45 mm
Height under ground: 600 mm
Slot height below ground line for cable entry: 150x50 mm
Weight: 80.2-115.2 kg
Finish: Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.