

Chara | Pole | Steel | Simple | Max 2 light sources



Ordering Information / Guide

Example: CH8300000-N-BM-EPR-GD2-HC0623-ZD140102-CN0

| Ground fixing     | Shape          | Top Set up / Light points                      | Height            | Section                           | Finish                      |
|-------------------|----------------|------------------------------------------------|-------------------|-----------------------------------|-----------------------------|
| BM<br>Buried root | EPR<br>Tapered | GD2<br>Suspended bracket   Max 2 light sources | HC0623<br>6230 mm | ZD140102<br>Base 140 - Top 102 mm | CN0<br>Grey [Neri] Textured |
| BF<br>Flanged     |                |                                                | HC0723<br>7230 mm |                                   |                             |
|                   |                |                                                | HC0823<br>8230 mm |                                   |                             |

Generated code: CH8300000 - N - \_ \_ \_ - \_ \_ \_ - \_ \_ \_ - \_ \_ \_ - \_ \_ \_ - \_ \_ \_ - \_ \_ \_ - \_ \_ \_

Chara | Pole | Steel | Simple | Max 2 light sources

MECHANICAL CHARACTERISTICS

Pole in S355 UNI EN 10219-1, pickled steel sheet and cast iron UNI EN 1561, all hot-dip galvanized according to UNI EN ISO 1461.  
CE-certified pole, compliant with standard UNI EN 40-5.

|                                               |                      |
|-----------------------------------------------|----------------------|
| Section                                       | Base/Top 140/102 mm  |
| Hatch size                                    | 350x100 mm           |
| Height under ground                           | 700 mm               |
| Slot height below ground line for cable entry | 150x50 mm            |
| Weight                                        | 93.8-129.1 kg        |
| Finish                                        | Grey [Neri] Textured |

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.