

Project location:

Project name:

Fixture type:

Qty:

Notes:

Chara | Pole | Steel | Simple | Max 2 light sources



Ordering Information / Guide

Example: CH8300000-N-BF-EPR-GD2-HC0623-ZD140102-CN0

| Ground fixing | Shape          | Top Set up / Light points                      | Height                                                                       | Section                               | Finish                      |
|---------------|----------------|------------------------------------------------|------------------------------------------------------------------------------|---------------------------------------|-----------------------------|
| BF<br>Flanged | EPR<br>Tapered | GD2<br>Suspended bracket   Max 2 light sources | HC0623<br>245.276 in<br><br>HC0723<br>284.646 in<br><br>HC0823<br>324.016 in | ZD140102<br>Base 5.512 - Top 4.016 in | CN0<br>Grey [Neri] Textured |

Generated code: CH8300000 - N - \_ \_ - \_ \_ - \_ \_ \_ \_ - \_ \_ \_ \_ \_

Chara | Pole | Steel | Simple | Max 2 light sources

MECHANICAL CHARACTERISTICS

Pole in S355 UNI EN 10219-1, pickled steel sheet and cast iron UNI EN 1561, all hot-dip galvanized according to UNI EN ISO 1461.  
CE-certified pole, compliant with standard UNI EN 40-5.

|            |                         |
|------------|-------------------------|
| Section    | Base/Top 5.512/4.016 in |
| Hatch size | 13.78x3.937 in          |
| Weight     | 206.79-274.03 lb        |
| Finish     | Grey [Neri] Textured    |

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.