


Polis Bollard | Luminaire | CARVE | H 16”



Ordering Information / Guide

Example: **BOPOL03-U-D54-927-L002-ST-V0-F06-MU-CN0**

Optics	Ra+K	Luminous flux	Lens	Voltage	Driver Function	ISO Class	Finish
D54 90°	927 Ra90 2700 K	L002 200 lm	ST Transparent	V0 120V-277V	F35 0-10V+CLO	MU UL	CN0 Grey [Neri] Textured
D53 180°	930 Ra90 3000 K	L005 500 lm			F45 DALI+CASAMBI		
D52 360°	940 Ra90 4000 K	L009 900 lm			F06 DALI+CLO		

Generated code: **BOPOL03 - U** - _ _ _ - _ _ _ - _ _ _ - _ _ _ - _ _ _ - _ _ _

CONFIGURATION NOTES
The product features shown in this datasheet cannot always be freely combined.
To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

Polis Bollard | Luminaire | CARVE | H 16”

SOURCE

Medium-power LED matrix.	
Energy-efficiency class	C, D
LED forward current	182-480 mA
Power rating	3.2-11.6 W
Nominal Flux	200-900 lm
Nominal CCT (Color temperature)	2700 K, 3000 K, 4000 K
Color Rendering Index (Ra)	90
Standard Deviation Colour Matching	≤5
Rated lifetime	L80 = 100000 h (Ts = 85 °C, 700 mA)

LIGHTING CHARACTERISTICS

Modular 2x2 refractive lenses in PMMA.	
Optics	90°, 180°, 360°
Optical efficiency	LOR = 100% ULOR = 1%
LED quantity	12, 24, 48
Cutoff Angle	Non Cutoff, Semi Cutoff C = 0° γ = 53, 54°
Luminous flux	200-900 lm
Luminous efficacy	39-68 lm/W
BUG	B=0-1, U=1, G=0
Photobiological safety	RG1 - Low risk

ELECTRICAL CHARACTERISTICS

Luminaire power	4.6-14.4 W
Voltage	120V-277V~ 50/60Hz
Power factor	≥0.99
Insulation class	UL
Control type - driver	0-10V+CLO, DALI+CASAMBI, DALI+CLO PstLM=<1 e SVM=<0,4 (IEC TR 61547-1 e IEC TR 63158)
Safe Flicker	
Ambient temperature	-13 °F / +122 °F
Driver included	Yes
Cable type	SJTW 5GAWG18
Cable length	3.281 ft
Surge protection	10kV CM - 10kV DM

MECHANICAL CHARACTERISTICS

Structure with an extruded aluminum outer frame and an integrated die-cast aluminum heat sink.	
Protective screen in extra-clear tempered transparent anti-reflective glass, exposed stainless steel or blackened screws, and plastic components.	
Body supported by galvanized steel sheet.	
Diameter	6.299 in
Height	15.748 in
Weight	15.43 lb
EPA	0.86 ft²
Protection degree	IP66
Mechanical resistance	IK10
Finish	Grey [Neri] Textured

INSTALLATION


Ground fixing using the appropriate flange.

WARNINGS


Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional.
Replaceable control gear by a professional.
Protection of surfaces: please refer to the specification on painting procedures of the materials.

Polis Bollard | Luminaire | CARVE | H 16”


Optic: 90°
Lens: Transparent



Optic: 180°
Lens: Transparent



Optic: 360°
Lens: Transparent



Polis Bollard | Luminaire | CARVE | H 16”

Optic: 90°

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
200 lm	2700 K	5.1	39	12	202	3.6	56	0	1	0
200 lm	3000 K	4.9	41	12	190	3.4	59	0	1	0
200 lm	4000 K	4.6	43	12	182	3.2	63	0	1	0

Optic: 180°

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
450 lm	2700 K	11.2	40	24	480	8.7	52	0	1	0
450 lm	3000 K	10.6	42	24	452	8.2	55	0	1	0
450 lm	4000 K	10.2	44	24	432	7.8	58	0	1	0

Optic: 360°

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
900 lm	2700 K	14.4	63	48	332	11.6	78	1	1	0
900 lm	3000 K	13.6	66	48	312	10.9	83	1	1	0
900 lm	4000 K	13.2	68	48	300	10.5	86	1	1	0