
NERI

Project location:	Fixture type: Qty:
Project name:	Notes:

POLIS BOLLARD | LUMINAIRE | CARVE | H 800 MM





IP66 IK10 Classe II

ORDERING INFORMATION / GUIDE

Example: **BOPOL04-N-D54-927-L003-ST-V1-F27-M2-CN0**

OPTIQUE	RA+K	LUMINOUS FLUX	SCREEN FINISH	POWER SUPPLY	DRIVER FUNCTION	ISO CLASS	FINISH
D54 90°	**927** Ra90 2700 K	**L003** 300 lm	**ST** Transparent	**V1** 220V-240V	**F27** ON/OFF+CLO	**M2** Class II	**CN0** Grey [Neri] Textured
D53 180°	**930** Ra90 3000 K	**L006** 600 lm			**F46** DALI+PIR		
D52 360°	**940** Ra90 4000 K	**L013** 1300 lm			**F06** DALI+CLO		
					F44 D4i+CASAMBI		

Generated code: **BOPOL04 - N** - _ _ _ - _ _ _ - _ _ _ _ - _ _ - _ _ - _ _ _ - _ _ - _ _ _

CONFIGURATION NOTES
The product features shown in this datasheet cannot always be freely combined.
To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

ON REQUEST
Non-standard variants and configurations available upon request. Please contact Neri for further information.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

POLIS BOLLARD | LUMINAIRE | CARVE | H 800 MM

SOURCE

Medium-power LED matrix.

Energy-efficiency class: C, D
LED forward current: 292-676 mA
Power rating: 5.4-17.3 W
Nominal Flux: 300-1250 lm
Nominal CCT (Colour temperature): 2700 K, 3000 K, 4000 K
Color Rendering Index (Ra): 90
Standard Deviation Colour Matching: ≤5
Rated lifetime: L80B50 100000 h @ Tq = 25 °C

LIGHTING CHARACTERISTICS

Modular 2x2 refractive lenses in PMMA.

Optique: 90°, 180°, 360°
Optical efficiency: LOR = 100% ULOR = 1%
LED quantity: 12, 24, 48
Cutoff Angle: Non Cutoff, Semi Cutoff C = 0° γ = 53, 54°
Luminous flux: 300-1250 lm
Luminous efficacy: 37-69 lm/W
Maximum luminous intensity γ 90°: ≤11.28 cd/klm
Luminous intensity class: G*2, G*3
IPEA: Road F / C, Urban F / C, Ped F / C, Park F / C, Art E / A
BUG: B=0-1, U=1, G=0-1
Photobiological safety: RG1 - Low risk

ELECTRICAL CHARACTERISTICS

ENEC safety mark.

Luminaire power: 7.1-20 W
Power supply: 220V-240V~ 50/60Hz
Power factor: ≥0.99
Insulation class: Class II
Control type - driver: ON/OFF+CLO, DALI+PIR, DALI+CLO, D4i+CASAMBI
Safe Flicker: PstLM=<1 e SVM=<0,4 (IEC TR 61547-1 e IEC TR 63158)
Ambient temperature: -25 °C / +50 °C
Driver included: Yes
Cable type: H07RN-F 2X1.5mm², H07RN-F 4X1.5mm²
Cable length: 1 m
Surge protection: 10kV CM - 6kV DM

MECHANICAL CHARACTERISTICS

Structure with an extruded aluminium outer frame and an integrated die-cast aluminium heat sink.
Protective screen in extra-clear tempered transparent anti-reflective glass, exposed stainless steel or blackened screws, and plastic components.
Body supported by galvanized steel sheet.

Diameter: 160 mm
Height: 800 mm
Weight: 9 kg
Wind-exposed area: 0.08 m²
Protection degree: IP66
Mechanical resistance: IK10
Finish: Grey [Neri] Textured

INSTALLATION

Ground fixing using the appropriate flange.

WARNINGS


Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional.
Replaceable control gear by a professional.
Protection of surfaces: please refer to the specification on painting procedures of the materials.


Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

POLIS BOLLARD | LUMINAIRE | CARVE | H 800 MM

Optic: 90°


Screen finish: Transparent






Optic: 180°


Screen finish: Transparent






Optic: 360°

Screen finish: Transparent





Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

POLIS BOLLARD | LUMINAIRE | CARVE | H 800 MM

Optic: 90° — **Screen finish:** Transparent

System					Source			IPEA				
Luminous Flux	**Nominal CCT**	**W**	**lm/W**	**n° led**	**mA**	**W**	**lm/W**	**Road**	**Urban**	**Ped**	**Park**	**Art**
300 lm	2700 K	8	37	12	324	6.1	49	F	F	F	F	E
300 lm	3000 K	7.5	40	12	306	5.7	53	F	E	F	F	E
300 lm	4000 K	7.1	42	12	292	5.4	56	E	E	E	E	E

Optic: 180° — **Screen finish:** Transparent

System					Source			IPEA				
Luminous Flux	**Nominal CCT**	**W**	**lm/W**	**n° led**	**mA**	**W**	**lm/W**	**Road**	**Urban**	**Ped**	**Park**	**Art**
600 lm	2700 K	15.4	39	24	676	12.9	47	F	E	F	F	E
600 lm	3000 K	14.4	42	24	636	12	50	E	E	E	E	E
600 lm	4000 K	13.8	43	24	608	11.4	53	E	E	E	E	D

Optic: 360° — **Screen finish:** Transparent

System					Source			IPEA				
Luminous Flux	**Nominal CCT**	**W**	**lm/W**	**n° led**	**mA**	**W**	**lm/W**	**Road**	**Urban**	**Ped**	**Park**	**Art**
1250 lm	2700 K	20	63	48	476	17.3	72	D	C	D	D	B
1250 lm	3000 K	18.9	66	48	452	16.2	77	C	C	C	C	B
1250 lm	4000 K	18.1	69	48	432	15.5	81	C	C	C	C	A

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.