NERI

Project location:	Fixture type: Qty:
Project name:	Notes:

PROPUS | POLE | STEEL | SIMPLE | MAX 2 LIGHT SOURCES



CE

ORDERING INFORMATION / GUIDE

Example**: PR1114000-N-BM-EPR-GD2-HC0600-ZD159089-CN0**

GROUND FIXING	SHAPE	TOP SET UP / LIGHT POINTS	HEIGHT	SECTION	FINISH
BM Buried root	**EPR** Tapered	**GD2** Suspended bracket | Max 2 light sources	**HC0600** 6000 mm	**ZD159089** Base 159 - Top 89 mm	**CN0** Grey [Neri] Textured
BF Flanged			**HC0700** 7000 mm	**ZD168089** Base 168 - Top 89 mm	
			HC0800 8000 mm		
			HC0900 9000 mm		

Generated code: **PR1114000 - N** - _ _ - _ _ _ - _ _ _ - _ _ _ _ _ _ - _ _ _ _ _ _ _ _ - _ _ _

CONFIGURATION NOTES
The product features shown in this datasheet cannot always be freely combined.
To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

ON REQUEST
Non-standard variants and configurations available upon request. Please contact Neri for further information.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

PROPUS | POLE | STEEL | SIMPLE | MAX 2 LIGHT SOURCES

MECHANICAL CHARACTERISTICS

Pole in steel UNI EN 10219, cast iron UNI EN-GJL-HB175 and aluminum casting EN 1706 AC-46100KF, hot-dip galvanized according to UNI EN ISO 1461.
CE-certified pole, compliant with standard UNI EN 40-5.

Section: Base/Top 159/89 mm, 168/89 mm
Hatch size: 186x45 mm

Height under ground: 100 mm, 600 mm, 800 mm
Slot height below ground line for cable entry: 150x50 mm
Weight: 72-138.5 kg
Finish: Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.