

Project location:



Project name:

Fixture type:

Qty:

Notes:

Pictor Bollard | Luminaire | H 24" | 1 light



Ordering Information / GuideExample: **BOPIC01-U-D36-830-L006-ST-V0-F27-MU-CN0**

Optics	Ra+K	Luminous flux	Lens	Voltage	Driver Function	ISO Class	Finish
D36 T2 medium	830 Ra80 3000 K	L006 600 lm	ST Transparent	V0 120V-277V	F27 ON/OFF+CLO	MU UL	CN0 Grey [Neri] Textured
D24 T4 wide	840 Ra80 4000 K	L010 1000 lm			F35 0-10V+CLO		

Generated code: **BOPIC01 - U** - _ _ _ _ _ - _ _ _ _ _ - _ _ _ _ _ - _ _ _ _ _ - _ _ _ _ _

Pictor Bollard | Luminaire | H 24” | 1 light

SOURCE

High-power LED matrix.	
Energy-efficiency class	D
LED forward current	172-334 mA
Power rating	3.6-7.2 W
Nominal Flux	550-1000 lm
Nominal CCT (Color temperature)	3000 K, 4000 K
Color Rendering Index (Ra)	80
Standard Deviation Colour Matching	≤5
ANSI/IES TM-30	Rf = 83-85 Rg = 95-96
Rated lifetime	L90 = 100000 h (Ts = 85 °C, 500 mA)

LIGHTING CHARACTERISTICS

Modular 2x2 refractive lenses in PMMA.	
Optics	T2 medium, T4 wide
Optical efficiency	LOR = 100% ULOR = 0%
LED quantity	8
Cutoff Angle	Cutoff, Semi Cutoff C = 20, 45° γ = 62, 66°
Luminous flux	550-1000 lm
Luminous efficacy	106-138 lm/W
BUG	B=0, U=0, G=0
Photobiological safety	RG1 - Low risk

ELECTRICAL CHARACTERISTICS

Luminaire power	4-9.4 W
Voltage	120V-277V~ 50/60Hz
Power factor	≥0.99
Insulation class	UL
Control type - driver	ON/OFF+CLO, 0-10V+CLO
Safe Flicker	PstLM=<1 e SVM=<0,4 (IEC TR 61547-1 e IEC TR 63158)
Ambient temperature	-31 °F / +95 °F
Driver included	Yes
Cable type	3GAWG18, 5GAWG18
Cable length	3.281 ft
Surge protection	20kV CM - 20kV DM

MECHANICAL CHARACTERISTICS


Structure with extruded aluminum outer frame, integrated aluminum die-cast heat sink, and extra-clear tempered glass protective screen with IK08 impact resistance (EN 62262).	
Steel sheet mounting bracket, fixing plug kit, and stainless steel and blackened screws.	
Body also supported by aluminum sheet.	
Length	9.646 in
Width	6.299 in
Height	23.622 in
Weight	25.35 lb
EPA	0.65 ft²
Protection degree	IP66
Mechanical resistance	IK08
Finish	Grey [Neri] Textured

WARNINGS


Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional.
Replaceable control gear by a professional.
Protection of surfaces: please refer to the specification on painting procedures of the materials.

Pictor Bollard | Luminaire | H 24” | 1 light

Optic: T2 medium
Lens: Transparent



Optic: T4 wide
Lens: Transparent



Pictor Bollard | Luminaire | H 24” | 1 light

Optic: T2 medium

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
550 lm	3000 K	5.1	108	8	180	3.8	145	0	0	0
550 lm	3000 K	4.2	131	8	180	3.8	145	0	0	0
550 lm	4000 K	4.9	112	8	172	3.6	153	0	0	0
550 lm	4000 K	4	138	8	172	3.6	153	0	0	0
1000 lm	3000 K	9.4	106	8	334	7.2	139	0	0	0
1000 lm	3000 K	8	125	8	334	7.2	139	0	0	0
1000 lm	4000 K	8.9	112	8	318	6.8	147	0	0	0
1000 lm	4000 K	7.6	132	8	318	6.8	147	0	0	0

Optic: T4 wide

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
550 lm	3000 K	5.1	108	8	180	3.8	145	0	0	0
550 lm	3000 K	4.2	131	8	180	3.8	145	0	0	0
550 lm	4000 K	4.9	112	8	172	3.6	153	0	0	0
550 lm	4000 K	4	137	8	172	3.6	153	0	0	0
1000 lm	3000 K	9.4	106	8	334	7.2	139	0	0	0
1000 lm	3000 K	8	125	8	334	7.2	139	0	0	0
1000 lm	4000 K	8.9	112	8	318	6.8	147	0	0	0
1000 lm	4000 K	7.6	132	8	318	6.8	147	0	0	0