NERI

| | | | |
|---|---|---|---|
| Project location: | | Fixture type: | Qty: |
| Project name: | | Notes: | |

## CHARA | POLE | STEEL | SIMPLE | MAX 2 LIGHT SOURCES



CE

## ORDERING INFORMATION / GUIDE

Example**: CH8300000-N-BM-EPR-GD2-HC0623-ZD140102-CN0**

| GROUND FIXING | SHAPE | TOP SET UP / LIGHT POINTS | HEIGHT | SECTION | FINISH |
|---|---|---|---|---|---|
| **BM**<br>Buried root | **EPR**<br>Tapered | **GD2**<br>Suspended bracket \| Max 2 light sources | **HC0623**<br>6230 mm | **ZD140102**<br>Base 140 - Top 102 mm | **CN0**<br>Grey [Neri] Textured |
| **BF**<br>Flanged | | | **HC0723**<br>7230 mm | | |
| | | | **HC0823**<br>8230 mm | | |

Generated code: **CH8300000 - N** - _ _ - _ _ _ - _ _ _ - _ _ _ - _ _ _ _ _ _ - _ _ _ _ _ _ _ _ _ - _ _ _

**ON REQUEST**
Non-standard variants and configurations available upon request. Please contact Neri for further information.


Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

## CHARA | POLE | STEEL | SIMPLE | MAX 2 LIGHT SOURCES

### MECHANICAL CHARACTERISTICS

Pole in S355 UNI EN 10219-1, pickled steel sheet and cast iron UNI EN 1561, all hot-dip galvanized according to UNI EN ISO 1461. CE-certified pole, compliant with standard UNI EN 40-5.

**Section:** Base/Top 140/102 mm
**Hatch size:** 350x100 mm
**Height under ground:** 700 mm

**Slot height below ground line for cable entry:** 150x50 mm
**Weight:** 93.8-129.1 kg
**Finish:** Grey [Neri] Textured

### WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.


Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.