NERI

Project location:		Fixture type:	Qty:
Project name:		Notes:	

KUMA | POLE | CAST IRON + STEEL | SIMPLE | MAX 4 LIGHT SOURCES



CE

ORDERING INFORMATION / GUIDE

Example**: KU1315000-N-BM-EPR-GA4-HC0540-ZD127102-CN0**

GROUND FIXING	SHAPE	TOP SET UP / LIGHT POINTS	HEIGHT	SECTION	FINISH
BM Buried root	**EPR** Tapered	**GA1** Bracket | Suspended swan neck | Max 1 light source	**HC0540** 5400 mm	**ZD127102** Base 127 - Top 102 mm	**CN0** Grey [Neri] Textured
BF Flanged		**GA4** Bracket | Suspended swan neck | Max 4 light sources	**HC0640** 6401 mm		

Generated code: **KU1315000 - N** - _ _ - _ _ _ - _ _ _ - _ _ _ - _ _ _ _ _ _ - _ _ _ _ _ _ _ _ - _ _ _

ON REQUEST
Non-standard variants and configurations available upon request. Please contact Neri for further information.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

KUMA | POLE | CAST IRON + STEEL | SIMPLE | MAX 4 LIGHT SOURCES

MECHANICAL CHARACTERISTICS

Pole in cast iron UNI EN 1561 and steel UNI EN 10219-1, hot-dip galvanized according to UNI EN ISO 1461.
CE-certified pole, compliant with standard UNI EN 40-5.

Section: Base/Top 127/102 mm
Hatch size: 186x45 mm
Height under ground: 800 mm

Slot height below ground line for cable entry: 150x50 mm
Weight: 138-162.3 kg
Finish: Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.