

Project location:

Project name:

Fixture type:

Qty:

Notes:

Kuma | Pole | Cast iron + Steel | Simple | Max 2 light sources



Ordering Information / Guide

Example: KU1300000-N-BM-EPR-GA2-HC0370-ZD152089-CN0

Ground fixing	Shape	Top Set up / Light points	Height	Section	Finish
BM Buried root	EPR Tapered	GA1 Bracket Suspended swan neck Max 1 light source	HC0370 3700 mm	ZD152089 Base 152 - Top 89 mm	CN0 Grey [Neri] Textured
BF Flanged		GA2 Bracket Suspended swan neck Max 2 light sources	HC0470 4700 mm		

Generated code: KU1300000 - N - _ _ - _ _ - _ _ _ _ _ - _ _ _ _ _ - _ _ _ _ _

Kuma | Pole | Cast iron + Steel | Simple | Max 2 light sources**MECHANICAL CHARACTERISTICS**

Pole in cast iron UNI EN 1561 and steel UNI EN 10219-1, hot-dip galvanized according to UNI EN ISO 1461.

CE-certified pole, compliant with standard UNI EN 40-5.

Section	Base/Top 152/89 mm
Hatch size	186x45 mm
Height under ground	600 mm
Slot height below ground line for cable entry	150x50 mm
Weight	80-91 kg
Finish	Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.