


Light 600 | Luminaire | Suspended



Ordering Information / Guide

Example: LU60001-U-D28-822-L015-SG-V0-F35-MU-CNO

Optics	Ra+K	Luminous flux	Lens	Voltage	Driver Function	ISO Class	Finish
D28 T1 short	822 Ra80 2200 K	L015 1500 lm	SG Frosted	V0 120V-277V	F35 0-10V+CLO	MU UL	CNO Grey [Neri] Textured
D36 T2 medium	827 Ra80 2700 K	L025 2500 lm					
D22 T3 narrow	830 Ra80 3000 K	L035 3500 lm					
D25 T2 narrow	840 Ra80 4000 K	L045 4500 lm					
D37 T3 medium		L060 6000 lm					
D24 T4 wide							
D38 T4 medium							
D30 T5 square medium							

Generated code: LU60001 - U - _ _ _ _ _

CONFIGURATION NOTES

The product features shown in this datasheet cannot always be freely combined.
To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

Light 600 | Luminaire | Suspended

SOURCE

High-power LED matrix.	
Energy-efficiency class	D, E
LED forward current	234-742 mA
Power rating	10-50 W
Nominal Flux	1500-6000 lm
Nominal CCT (Color temperature)	2200 K, 2700 K, 3000 K, 4000 K
Color Rendering Index (Ra)	80
Standard Deviation Colour Matching	≤5
ANSI/IES TM-30	Rf = 83-86 Rg = 95-96
Rated lifetime	L90 = 100000 h (Ts = 85 °C, 700 mA)

LIGHTING CHARACTERISTICS

Modular 2x2 refractive lenses in PMMA.	
Optics	T1 short, T2 medium, T3 narrow, T2 narrow, T3 medium, T4 wide, T4 medium, T5 square medium
	LOR = 100% ULOR = 7%
Optical efficiency	16, 24
LED quantity	Non Cutoff, Semi Cutoff C = 10, 50° γ = 56, 66°
Cutoff Angle	
Luminous flux	1500-6000 lm
Luminous efficacy	93-123 lm/W
BUG	B=1-2, U=3, G=1-2
Photobiological safety	RG1 - Low risk

ELECTRICAL CHARACTERISTICS

Luminaire power	12.2-58.3 W
Voltage	120V-277V~ 50/60Hz
Power factor	≥0.99
Insulation class	UL
Control type - driver	0-10V+CLO
Safe Flicker	PstLM=<1 e SVM=<0,4 (IEC TR 61547-1 e IEC TR 63158)
Ambient temperature	-22 °F / +122 °F
Driver included	Yes
Surge protection	20kV CM - 20kV DM

MECHANICAL CHARACTERISTICS

Structure made of die-cast aluminum (UNI EN 1706) with an upper circular tilting frame, hinged to the lower frame and equipped with a decorative finial.	
Lower frame consisting of two rings and three decorative uprights, connected in a tripod with a decorative finial.	
Full basket shield in satin-finished polymethyl methacrylate (PMMA) with IK06 impact resistance (EN 62262) and stainless steel screws.	
Diameter	18.504 in
Height	37.795 in
Weight	28.66 lb
EPA	1.83 ft²
Protection degree	IP43
Mechanical resistance	IK06
Finish	Grey [Neri] Textured

INSTALLATION

Suspended: threaded connection G3/4".


WARNINGS

Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional.
Replaceable control gear by a professional.
Protection of surfaces: please refer to the specification on painting procedures of the materials.

Light 600 | Luminaire | Suspended


Optic: T1 short

Lens: Frosted




Optic: T2 medium

Lens: Frosted




Optic: T3 narrow

Lens: Frosted




Optic: T2 narrow

Lens: Frosted




Optic: T3 medium

Lens: Frosted




Optic: T4 wide

Lens: Frosted




Optic: T4 medium

Lens: Frosted



Optic: T5 square medium

Lens: Frosted



Light 600 | Luminaire | Suspended

Optic: T1 short

Lens: Frosted

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
1500 lm	2200 K	15	100	16	288	12.4	121	1	3	1
1500 lm	2700 K	13.6	110	16	260	11.2	134	1	3	1
1500 lm	3000 K	12.9	116	16	248	10.6	142	1	3	1
1500 lm	4000 K	12.2	123	16	234	10	150	1	3	1
2500 lm	2200 K	25.9	97	16	494	21.7	115	1	3	1
2500 lm	2700 K	23.3	107	16	446	19.5	128	1	3	1
2500 lm	3000 K	22.1	113	16	422	18.4	136	1	3	1
2500 lm	4000 K	20.9	120	16	400	17.4	144	1	3	1
3500 lm	2200 K	37.5	93	16	714	32	109	1	3	1
3500 lm	2700 K	33.6	104	16	640	28.5	123	1	3	1
3500 lm	3000 K	31.9	110	16	608	27	130	1	3	1
3500 lm	4000 K	30.1	116	16	574	25.4	138	1	3	1
4500 lm	2200 K	47.5	95	24	602	40.1	112	2	3	1
4500 lm	2700 K	42.8	105	24	542	35.9	125	2	3	1
4500 lm	3000 K	40.6	111	24	514	33.9	133	2	3	1
4500 lm	4000 K	38.4	117	24	486	32	141	2	3	1
6000 lm	2700 K	58.3	103	24	742	50	120	2	3	2
6000 lm	3000 K	55.2	109	24	702	47.2	127	2	3	2
6000 lm	4000 K	52.3	115	24	664	44.5	135	2	3	2

Optic: T2 medium

Lens: Frosted

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
1500 lm	2200 K	15	100	16	288	12.4	121	1	3	1
1500 lm	2700 K	13.6	110	16	260	11.2	134	1	3	1
1500 lm	3000 K	12.9	116	16	248	10.6	142	1	3	1
1500 lm	4000 K	12.2	123	16	234	10	150	1	3	1
2500 lm	2200 K	25.9	97	16	494	21.7	115	1	3	1
2500 lm	2700 K	23.3	107	16	446	19.5	128	1	3	1
2500 lm	3000 K	22.1	113	16	422	18.4	136	1	3	1
2500 lm	4000 K	20.9	120	16	400	17.4	144	1	3	1
3500 lm	2200 K	37.5	93	16	714	32	109	1	3	1
3500 lm	2700 K	33.6	104	16	640	28.5	123	1	3	1
3500 lm	3000 K	31.9	110	16	608	27	130	1	3	1
3500 lm	4000 K	30.1	116	16	574	25.4	138	1	3	1
4500 lm	2200 K	47.5	95	24	602	40.1	112	1	3	2
4500 lm	2700 K	42.8	105	24	542	35.9	125	1	3	2
4500 lm	3000 K	40.6	111	24	514	33.9	133	1	3	2
4500 lm	4000 K	38.4	117	24	486	32	141	1	3	2
6000 lm	2700 K	58.3	103	24	742	50	120	1	3	2
6000 lm	3000 K	55.2	109	24	702	47.2	127	1	3	2
6000 lm	4000 K	52.3	115	24	664	44.5	135	1	3	2

Light 600 | Luminaire | Suspended

Optic: T3 narrow

Lens: Frosted

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
1500 lm	2200 K	15	100	16	288	12.4	121	1	3	1
1500 lm	2700 K	13.6	110	16	260	11.2	134	1	3	1
1500 lm	3000 K	12.9	116	16	248	10.6	142	1	3	1
1500 lm	4000 K	12.2	123	16	234	10	150	1	3	1
2500 lm	2200 K	25.9	97	16	494	21.7	115	1	3	1
2500 lm	2700 K	23.3	107	16	446	19.5	128	1	3	1
2500 lm	3000 K	22.1	113	16	422	18.4	136	1	3	1
2500 lm	4000 K	20.9	120	16	400	17.4	144	1	3	1
3500 lm	2200 K	37.5	93	16	714	32	109	1	3	1
3500 lm	2700 K	33.6	104	16	640	28.5	123	1	3	1
3500 lm	3000 K	31.9	110	16	608	27	130	1	3	1
3500 lm	4000 K	30.1	116	16	574	25.4	138	1	3	1
4500 lm	2200 K	47.5	95	24	602	40.1	112	1	3	2
4500 lm	2700 K	42.8	105	24	542	35.9	125	1	3	2
4500 lm	3000 K	40.6	111	24	514	33.9	133	1	3	2
4500 lm	4000 K	38.4	117	24	486	32	141	1	3	2
6000 lm	2700 K	58.3	103	24	742	50	120	2	3	2
6000 lm	3000 K	55.2	109	24	702	47.2	127	2	3	2
6000 lm	4000 K	52.3	115	24	664	44.5	135	2	3	2

Optic: T2 narrow

Lens: Frosted

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
1500 lm	2200 K	15	100	16	288	12.4	121	1	3	1
1500 lm	2700 K	13.6	110	16	260	11.2	134	1	3	1
1500 lm	3000 K	12.9	116	16	248	10.6	142	1	3	1
1500 lm	4000 K	12.2	123	16	234	10	150	1	3	1
2500 lm	2200 K	25.9	97	16	494	21.7	115	1	3	1
2500 lm	2700 K	23.3	107	16	446	19.5	128	1	3	1
2500 lm	3000 K	22.1	113	16	422	18.4	136	1	3	1
2500 lm	4000 K	20.9	120	16	400	17.4	144	1	3	1
3500 lm	2200 K	37.5	93	16	714	32	109	1	3	2
3500 lm	2700 K	33.6	104	16	640	28.5	123	1	3	2
3500 lm	3000 K	31.9	110	16	608	27	130	1	3	2
3500 lm	4000 K	30.1	116	16	574	25.4	138	1	3	2
4500 lm	2200 K	47.5	95	24	602	40.1	112	1	3	2
4500 lm	2700 K	42.8	105	24	542	35.9	125	1	3	2
4500 lm	3000 K	40.6	111	24	514	33.9	133	1	3	2
4500 lm	4000 K	38.4	117	24	486	32	141	1	3	2
6000 lm	2700 K	58.3	103	24	742	50	120	2	3	2
6000 lm	3000 K	55.2	109	24	702	47.2	127	2	3	2
6000 lm	4000 K	52.3	115	24	664	44.5	135	2	3	2

Light 600 | Luminaire | Suspended

Optic: T3 medium

Lens: Frosted

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
1500 lm	2200 K	15	100	16	288	12.4	121	1	3	1
1500 lm	2700 K	13.6	110	16	260	11.2	134	1	3	1
1500 lm	3000 K	12.9	116	16	248	10.6	142	1	3	1
1500 lm	4000 K	12.2	123	16	234	10	150	1	3	1
2500 lm	2200 K	25.9	97	16	494	21.7	115	1	3	1
2500 lm	2700 K	23.3	107	16	446	19.5	128	1	3	1
2500 lm	3000 K	22.1	113	16	422	18.4	136	1	3	1
2500 lm	4000 K	20.9	120	16	400	17.4	144	1	3	1
3500 lm	2200 K	37.5	93	16	714	32	109	1	3	2
3500 lm	2700 K	33.6	104	16	640	28.5	123	1	3	2
3500 lm	3000 K	31.9	110	16	608	27	130	1	3	2
3500 lm	4000 K	30.1	116	16	574	25.4	138	1	3	2
4500 lm	2200 K	47.5	95	24	602	40.1	112	1	3	2
4500 lm	2700 K	42.8	105	24	542	35.9	125	1	3	2
4500 lm	3000 K	40.6	111	24	514	33.9	133	1	3	2
4500 lm	4000 K	38.4	117	24	486	32	141	1	3	2
6000 lm	2700 K	58.3	103	24	742	50	120	2	3	2
6000 lm	3000 K	55.2	109	24	702	47.2	127	2	3	2
6000 lm	4000 K	52.3	115	24	664	44.5	135	2	3	2

Optic: T4 wide

Lens: Frosted

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
1500 lm	2200 K	15	100	16	288	12.4	121	1	3	1
1500 lm	2700 K	13.6	110	16	260	11.2	134	1	3	1
1500 lm	3000 K	12.9	116	16	248	10.6	142	1	3	1
1500 lm	4000 K	12.2	123	16	234	10	150	1	3	1
2500 lm	2200 K	25.9	97	16	494	21.7	115	1	3	1
2500 lm	2700 K	23.3	107	16	446	19.5	128	1	3	1
2500 lm	3000 K	22.1	113	16	422	18.4	136	1	3	1
2500 lm	4000 K	20.9	120	16	400	17.4	144	1	3	1
3500 lm	2200 K	37.5	93	16	714	32	109	1	3	2
3500 lm	2700 K	33.6	104	16	640	28.5	123	1	3	2
3500 lm	3000 K	31.9	110	16	608	27	130	1	3	2
3500 lm	4000 K	30.1	116	16	574	25.4	138	1	3	2
4500 lm	2200 K	47.5	95	24	602	40.1	112	1	3	2
4500 lm	2700 K	42.8	105	24	542	35.9	125	1	3	2
4500 lm	3000 K	40.6	111	24	514	33.9	133	1	3	2
4500 lm	4000 K	38.4	117	24	486	32	141	1	3	2
6000 lm	2700 K	58.3	103	24	742	50	120	2	3	2
6000 lm	3000 K	55.2	109	24	702	47.2	127	2	3	2
6000 lm	4000 K	52.3	115	24	664	44.5	135	2	3	2

Light 600 | Luminaire | Suspended

Optic: T4 medium

Lens: Frosted

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
1500 lm	2200 K	15	100	16	288	12.4	121	1	3	1
1500 lm	2700 K	13.6	110	16	260	11.2	134	1	3	1
1500 lm	3000 K	12.9	116	16	248	10.6	142	1	3	1
1500 lm	4000 K	12.2	123	16	234	10	150	1	3	1
2500 lm	2200 K	25.9	97	16	494	21.7	115	1	3	1
2500 lm	2700 K	23.3	107	16	446	19.5	128	1	3	1
2500 lm	3000 K	22.1	113	16	422	18.4	136	1	3	1
2500 lm	4000 K	20.9	120	16	400	17.4	144	1	3	1
3500 lm	2200 K	37.5	93	16	714	32	109	1	3	1
3500 lm	2700 K	33.6	104	16	640	28.5	123	1	3	1
3500 lm	3000 K	31.9	110	16	608	27	130	1	3	1
3500 lm	4000 K	30.1	116	16	574	25.4	138	1	3	1
4500 lm	2200 K	47.5	95	24	602	40.1	112	1	3	2
4500 lm	2700 K	42.8	105	24	542	35.9	125	1	3	2
4500 lm	3000 K	40.6	111	24	514	33.9	133	1	3	2
4500 lm	4000 K	38.4	117	24	486	32	141	1	3	2
6000 lm	2700 K	58.3	103	24	742	50	120	2	3	2
6000 lm	3000 K	55.2	109	24	702	47.2	127	2	3	2
6000 lm	4000 K	52.3	115	24	664	44.5	135	2	3	2

Optic: T5 square medium

Lens: Frosted

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
1500 lm	2200 K	15	100	16	288	12.4	121	1	3	1
1500 lm	2700 K	13.6	110	16	260	11.2	134	1	3	1
1500 lm	3000 K	12.9	116	16	248	10.6	142	1	3	1
1500 lm	4000 K	12.2	123	16	234	10	150	1	3	1
2500 lm	2200 K	25.9	97	16	494	21.7	115	1	3	1
2500 lm	2700 K	23.3	107	16	446	19.5	128	1	3	1
2500 lm	3000 K	22.1	113	16	422	18.4	136	1	3	1
2500 lm	4000 K	20.9	120	16	400	17.4	144	1	3	1
3500 lm	2200 K	37.5	93	16	714	32	109	2	3	1
3500 lm	2700 K	33.6	104	16	640	28.5	123	2	3	1
3500 lm	3000 K	31.9	110	16	608	27	130	2	3	1
3500 lm	4000 K	30.1	116	16	574	25.4	138	2	3	1
4500 lm	2200 K	47.5	95	24	602	40.1	112	2	3	2
4500 lm	2700 K	42.8	105	24	542	35.9	125	2	3	2
4500 lm	3000 K	40.6	111	24	514	33.9	133	2	3	2
4500 lm	4000 K	38.4	117	24	486	32	141	2	3	2
6000 lm	2700 K	58.3	103	24	742	50	120	2	3	2
6000 lm	3000 K	55.2	109	24	702	47.2	127	2	3	2
6000 lm	4000 K	52.3	115	24	664	44.5	135	2	3	2