

Matar | Pole | Steel + Aluminium | Tapered | Max 2 light sources



Ordering Information / Guide

Example: **MA1113000-N-BM-EPR-GD2-HC0500-ZD140089-CNO**

Ground fixing	Shape	Top Set up / Light points	Height	Section	Finish
BM Buried root	EPR Tapered	GD2 Suspended bracket Max 2 light sources	HC0500 5000 mm	ZD140089 Base 140 - Top 89 mm	CNO Grey [Neri] Textured
BF Flanged			HC0600 6000 mm	ZD159089 Base 159 - Top 89 mm	
			HC0700 7000 mm	ZD168089 Base 168 - Top 89 mm	
			HC0800 8000 mm		
			HC0900 9000 mm		
			HC1000 10000 mm		

Generated code: **MA1113000 - N** - _ _ - _ _ - _ _ _ _ - _ _ _ _ _ - _ _ _

CONFIGURATION NOTES
The product features shown in this datasheet cannot always be freely combined.
To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

Matar | Pole | Steel + Aluminium | Tapered | Max 2 light sources**MECHANICAL CHARACTERISTICS**

Pole in steel UNI EN 10219 and aluminum casting EN 1706 AC-46100KF, hot-dip galvanized according to UNI EN ISO 1461.

CE-certified pole, compliant with standard UNI EN 40-5.

Section	Base/Top 140/89 mm, 159/89 mm, 168/89 mm
Hatch size	186x45 mm
Height under ground	100 mm, 600 mm, 800 mm
Slot height below ground line for cable entry	150x50 mm
Weight	46.5-143 kg
Finish	Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.