



Example: **AL8102000-N-BM-EPD-GE2-HC0228-ZD114060-CN0**

Ground fixing	Shape	Top Set up / Light points	Height	Section	Finish
BM Buried root	EPD Decorated	GE2 Suspended swan neck Max 2 light sources	HC0228 2280 mm	ZD102060 Base 102 - Top 60 mm	CN0 Grey [Neri] Textured
BF Flanged				ZD114060 Base 114 - Top 60 mm	

Generated code: AL8102000 - N - _ _ - _ _ - _ _ - _ _ - _ _

The product features shown in this datasheet cannot always be freely combined.

To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

Alcor | Pole | Cast iron + Steel | Small | Max 2 light sources**MECHANICAL CHARACTERISTICS**

Modular pole made of cast iron UNI EN 1561, spheroidal graphite cast iron UNI EN 1563 and steel, with internal core in S355 UNI EN 10219-1, hot-dip galvanized according to UNI EN ISO 1461.

CE-certified pole, compliant with standard UNI EN 40-5.

Section	Base/Top 102/60 mm, 114/60 mm
Hatch size	50x50 mm
Height under ground	600 mm
Slot height below ground line for cable entry	150x50 mm
Weight	80-81 kg
Finish	Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.