NERI

Project location:		Fixture type:	Qty:
Project name:		Notes:	

MATAR | POLE | STEEL + ALUMINIUM | SIMPLE | MAX 2 LIGHT SOURCES



CE

ORDERING INFORMATION / GUIDE

Example**: MA1121000-N-BF-EPR-GD2-HC0600-ZD127089-CN0**

GROUND FIXING	SHAPE	TOP SET UP / LIGHT POINTS	HEIGHT	SECTION	FINISH
BF Flanged	**EPR** Tapered	**GD1** Suspended bracket | Max 1 light source	**HC0600** 236.221 in	**ZD127089** Base 5 - Top 3.504 in	**CN0** Grey [Neri] Textured
		GD2 Suspended bracket | Max 2 light sources	**HC0700** 275.591 in	**ZD140089** Base 5.512 - Top 3.504 in	
			HC0800 314.961 in		

Generated code: **MA1121000 - N** - _ _ - _ _ _ - _ _ _ - _ _ _ _ _ _ - _ _ _ _ _ _ _ _ _ - _ _ _

CONFIGURATION NOTES
The product features shown in this datasheet cannot always be freely combined.
To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

ON REQUEST
Non-standard variants and configurations available upon request. Please contact Neri for further information.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.

MATAR | POLE | STEEL + ALUMINIUM | SIMPLE | MAX 2 LIGHT SOURCES

MECHANICAL CHARACTERISTICS

Pole in steel UNI EN 10219 and aluminum casting EN 1706 AC-46100KF, hot-dip galvanized according to UNI EN ISO 1461.
CE-certified pole, compliant with standard UNI EN 40-5.

Section: Base/Top 5.512/3.504 in, 5/3.504 in
Hatch size: 7.323x1.772 in

Height under ground: 3.937 in
Weight: 139.11-250.89 lb
Finish: Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.

Property of Neri S.p.A. - Reproduction and use for unauthorized purposes is prohibited.
Neri reserves the right to make changes to its products and documentation without prior notice.