

Simple for swan necks | Pole | Cast iron + Steel | Simple | Max 4 light sources



Ordering Information / Guide

Example: SP1122000-N-BM-EPR-GD2-HC0370-ZD102089-CN0

Ground fixing	Shape	Top Set up / Light points	Height	Section	Finish
BM Buried root	EPR Tapered	GD1 Suspended bracket Max 1 light source	HC0370 3700 mm	ZD102089 Base 102 - Top 89 mm	CN0 Grey [Neri] Textured
		GD2 Suspended bracket Max 2 light sources	HC0470 4700 mm	ZD127102 Base 127 - Top 102 mm	
		GD4 Suspended bracket Max 4 light sources	HC0540 5400 mm		
			HC0640 6401 mm		

Generated code: SP1122000 - N - _ _ - _ _ - _ _ _ _ - _ _ _ _ _ - _ _ _ _

CONFIGURATION NOTES
The product features shown in this datasheet cannot always be freely combined.
To verify the configurations actually available and define the corresponding product code, please use the configurator available on our website.

Simple for swan necks | Pole | Cast iron + Steel | Simple | Max 4 light sources

MECHANICAL CHARACTERISTICS

Pole in cast iron UNI EN 1561 and steel UNI EN 10219-1, hot-dip galvanized according to UNI EN ISO 1461.

CE-certified pole, compliant with standard UNI EN 40-5.

Section Base/Top 102/89 mm, 127/102 mm

Hatch size 132x38 mm, 186x45 mm

Height under ground 600 mm, 800 mm

Slot height below ground line for cable entry 150x50 mm

Weight 41-102 kg

Finish Grey [Neri] Textured

WARNINGS

Protection of surfaces: please refer to the specification on painting procedures of the materials.