

Generated code: **LUANT01-U** - - - - -

Page 1 of 28

Antares | Luminaire | Antares L

SOURCE

High-power LED matrix.	
Energy-efficiency class	, C, D
LED forward current	368-906 mA
Power rating	39.8-154.4 W
Nominal Flux	4000-24000 lm
Nominal CCT (Color temperature)	2700 K, 3000 K, 4000 K, Amber
Color Rendering Index (Ra)	70
Standard Deviation Colour Matching	≤5

LIGHTING CHARACTERISTICS

Modular 2x2 refractive lenses in PMMA.	
Optics	T1 short, AFR/SPORT N, T2 medium, T2 medium + BLC, AFR/SPORT W, AFR/ SPORT W + BLC, T2 wide, T3 narrow, T3 narrow + BLC, T2 narrow, T3 medium, T3 medium + BLC, T4 wide, T4 wide + BLC, T4 medium, T4 medium + BLC, T5 square medium, T5 Round, Left corner, Right corner LOR = 65-100% ULOR = 0%
Optical efficiency	40, 60
LED quantity	Cutoff, Semi Cutoff C = 0, 155° γ = 13, 68°
Cutoff Angle	
Luminous flux	2611-24000 lm
Luminous efficacy	22-162 lm/W
BUG	B=1-4, U=0, G=0-3

ELECTRICAL CHARACTERISTICS

Luminaire power	47.1-171.4 W
Voltage	120V-277V~ 50/60Hz, 347V-480V~ 50/60Hz
Power factor	≥0.99
Insulation class	UL
Control type - driver	0-10V+CLO, 1-10V+PIR, NEMA-3, NEMA-7
Surge protection	20kV CM - 20kV DM

MECHANICAL CHARACTERISTICS

Structure made of die-cast aluminum (UNI EN 1706) with an openable upper frame for access to the auxiliary compartment and an integrated heat sink. Shield in extra-clear tempered glass with IK08 impact resistance (EN 62262). Internal white reflector in polycarbonate, silicone seal between lower frame and upper cover, stainless steel screws, and osmotic valve for pressure balancing.	
Provision for additional surge protectors or remote monitoring systems.	
Length	30.118 in
Width	13.386 in
Height	10.354 in
Weight	28.66 lb
EPA	0.32 ft²
Finish	Grey [Neri] Textured

INSTALLATION

Suitable for side mounting or pole-top installation on Ø 1-7/8" tubes and Ø 2-3/8" tubes.
Adjustable from 0°/+20° in pole-top configuration, from -5°/+15° in bracket configuration.


WARNINGS

Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional.
Replaceable control gear by a professional.
Protection of surfaces: please refer to the specification on painting procedures of the materials.

Antares | Luminaire | Antares L


Optic: T1 short

Lens: Transparent




Optic: AFR/SPORT N

Lens: Transparent




Optic: T2 medium

Lens: Transparent




Optic: T2 medium + BLC

Lens: Transparent




Optic: AFR/SPORT W

Lens: Transparent




Optic: AFR/SPORT W + BLC

Lens: Transparent




Optic: T2 wide

Lens: Transparent



Optic: T3 narrow


Lens: Transparent



Antares | Luminaire | Antares L


Optic: T3 narrow + BLC

Lens: Transparent




Optic: T2 narrow

Lens: Transparent




Optic: T3 medium

Lens: Transparent




Optic: T3 medium + BLC

Lens: Transparent




Optic: T4 wide

Lens: Transparent




Optic: T4 wide + BLC

Lens: Transparent




Optic: T4 medium

Lens: Transparent




Optic: T4 medium + BLC

Lens: Transparent




Antares | Luminaire | Antares L


Optic: T5 square medium
Lens: Transparent




Optic: T5 Round
Lens: Transparent



Optic: Left corner
Lens: Transparent




Optic: Right corner
Lens: Transparent




Amber

Optic: T1 short
Lens: Transparent



Optic: AFR/SPORT N
Lens: Transparent




Antares | Luminaire | Antares L

Amber


Optic: T2 medium

Lens: Transparent




Optic: T2 medium + BLC

Lens: Transparent




Optic: AFR/SPORT W

Lens: Transparent




Optic: AFR/SPORT W + BLC

Lens: Transparent




Optic: T2 wide

Lens: Transparent



Optic: T3 narrow

Lens: Transparent




Antares | Luminaire | Antares L

Amber


Optic: T3 narrow + BLC

Lens: Transparent




Optic: T2 narrow

Lens: Transparent




Optic: T3 medium

Lens: Transparent




Optic: T3 medium + BLC

Lens: Transparent




Optic: T4 wide

Lens: Transparent



Optic: T4 wide + BLC


Lens: Transparent




Antares | Luminaire | Antares L

Amber


Optic: T4 medium
Lens: Transparent




Optic: T4 medium + BLC
Lens: Transparent




Optic: T5 square medium
Lens: Transparent




Optic: T5 Round
Lens: Transparent



Optic: Left corner
Lens: Transparent



Optic: Right corner
Lens: Transparent



Antares | Luminaire | Antares L

Optic: T1 short

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	2	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	2
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	2
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	2
9000 lm	2700 K	61.2	147	40	480	52.7	171	3	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	3	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	3	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	3	0	3
10500 lm	3000 K	70.1	150	40	552	61	172	3	0	3
10500 lm	4000 K	66.8	157	40	526	57.9	181	3	0	3
12000 lm	2700 K	83.1	144	40	656	73.2	164	3	0	3
12000 lm	3000 K	80.8	149	40	638	71.1	169	3	0	3
12000 lm	4000 K	77	156	40	608	67.5	178	3	0	3
13500 lm	2700 K	94.6	143	40	748	84.1	161	3	0	3
13500 lm	3000 K	91.9	147	40	726	81.5	166	3	0	3
13500 lm	4000 K	87.6	154	40	692	77.4	174	3	0	3
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	3
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	3
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	3
18000 lm	2700 K	124.2	145	60	656	109.9	164	4	0	3
18000 lm	3000 K	120.6	149	60	638	106.6	169	4	0	3
18000 lm	4000 K	114.6	157	60	608	101.2	178	4	0	3
21000 lm	2700 K	147.7	142	60	780	131.6	160	4	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	4	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	4	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	4	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	4	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	4	0	3

Antares | Luminaire | Antares L

Optic: AFR/SPORT N

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	1
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	1
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	1
10500 lm	2700 K	72	146	40	568	62.8	167	3	0	1
10500 lm	3000 K	70.1	150	40	552	61	172	3	0	1
10500 lm	4000 K	66.8	157	40	526	57.9	181	3	0	1
12000 lm	2700 K	83.1	144	40	656	73.2	164	3	0	1
12000 lm	3000 K	80.8	149	40	638	71.1	169	3	0	1
12000 lm	4000 K	77	156	40	608	67.5	178	3	0	1
13500 lm	2700 K	94.6	143	40	748	84.1	161	3	0	1
13500 lm	3000 K	91.9	147	40	726	81.5	166	3	0	1
13500 lm	4000 K	87.6	154	40	692	77.4	174	3	0	1
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	2
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	2
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	2
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	2
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	2
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	2
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	2
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	2
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	2

Antares | Luminaire | Antares L

Optic: T2 medium

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	1
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	1
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	1
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	2	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	2	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	2	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	2
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	2
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	2
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: T2 medium + BLC

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	1	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	1	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	1	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	1
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	1
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	1
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	2	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	2	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	2	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	2	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	2	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	2	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	2
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	2
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	2
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	2
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	2
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	2
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	2
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	2
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	2

Antares | Luminaire | Antares L

Optic: AFR/SPORT W

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	3	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	3	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	3	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	3	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	3	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	3	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	3
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	3
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	3
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: AFR/SPORT W + BLC

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	1
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	1
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	1
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	1
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	1
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	1
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	3	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	3	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	3	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	2
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	2
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	2
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	2
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	2
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	2
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: T2 wide

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	2	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	2	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	2	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	2	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	2	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	2	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	3
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	3
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	3
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: T3 narrow

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	1
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	1
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	1
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	3	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	3	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	3	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	2
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	2
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	2
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: T3 narrow + BLC

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	27	60	750	103.8	39	1	0	0
7500 lm	2700 K	50.8	116	40	396	43.1	174	1	0	1
7500 lm	3000 K	49.4	119	40	386	41.8	179	1	0	1
7500 lm	4000 K	47.1	125	40	368	39.8	188	1	0	1
9000 lm	2700 K	61.2	115	40	480	52.7	171	1	0	1
9000 lm	3000 K	59.6	118	40	468	51.2	176	1	0	1
9000 lm	4000 K	56.9	124	40	446	48.7	185	1	0	1
10500 lm	2700 K	72	114	40	568	62.8	167	1	0	1
10500 lm	3000 K	70.1	117	40	552	61	172	1	0	1
10500 lm	4000 K	66.8	123	40	526	57.9	181	1	0	1
12000 lm	2700 K	83.1	113	40	656	73.2	164	2	0	1
12000 lm	3000 K	80.8	116	40	638	71.1	169	2	0	1
12000 lm	4000 K	77	122	40	608	67.5	178	2	0	1
13500 lm	2700 K	94.6	112	40	748	84.1	161	2	0	1
13500 lm	3000 K	91.9	115	40	726	81.5	166	2	0	1
13500 lm	4000 K	87.6	121	40	692	77.4	174	2	0	1
15000 lm	2700 K	100	118	60	538	89.1	168	2	0	2
15000 lm	3000 K	97.2	121	60	524	86.5	173	2	0	2
15000 lm	4000 K	92.7	127	60	498	82.3	182	2	0	2
18000 lm	2700 K	124.2	114	60	656	109.9	164	2	0	2
18000 lm	3000 K	120.6	117	60	638	106.6	169	2	0	2
18000 lm	4000 K	114.6	123	60	608	101.2	178	2	0	2
21000 lm	2700 K	147.7	112	60	780	131.6	160	2	0	2
21000 lm	3000 K	143.4	115	60	756	127.6	165	2	0	2
21000 lm	4000 K	136.4	121	60	720	121.1	173	2	0	2
24000 lm	2700 K	171.4	110	60	906	154.4	155	3	0	2
24000 lm	3000 K	166.4	113	60	878	149.6	160	3	0	2
24000 lm	4000 K	158.4	119	60	836	141.8	169	3	0	2

Antares | Luminaire | Antares L

Optic: T2 narrow

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	2
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	2
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	2
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	2	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	2	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	2	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	3
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	3
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	3
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	3
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	3
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	3
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: T3 medium

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	2	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	2	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	2	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	3
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	3
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	3
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: T3 medium + BLC

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	1	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	1	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	1	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	1	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	1	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	1	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	2	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	2	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	2	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	2	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	2	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	2	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	2	0	2
18000 lm	3000 K	120.6	149	60	638	106.6	169	2	0	2
18000 lm	4000 K	114.6	157	60	608	101.2	178	2	0	2
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	2
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	2
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	2
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: T4 wide

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	2
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	2
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	2
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	2	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	2	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	2	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	2	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	2	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	2	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	3
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	3
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	3
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: T4 wide + BLC

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	22	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	96	40	396	43.1	174	1	0	1
7500 lm	3000 K	49.4	99	40	386	41.8	179	1	0	1
7500 lm	4000 K	47.1	104	40	368	39.8	188	1	0	1
9000 lm	2700 K	61.2	96	40	480	52.7	171	1	0	1
9000 lm	3000 K	59.6	99	40	468	51.2	176	1	0	1
9000 lm	4000 K	56.9	103	40	446	48.7	185	1	0	1
10500 lm	2700 K	72	95	40	568	62.8	167	1	0	2
10500 lm	3000 K	70.1	98	40	552	61	172	1	0	2
10500 lm	4000 K	66.8	103	40	526	57.9	181	1	0	2
12000 lm	2700 K	83.1	94	40	656	73.2	164	1	0	2
12000 lm	3000 K	80.8	97	40	638	71.1	169	1	0	2
12000 lm	4000 K	77	102	40	608	67.5	178	1	0	2
13500 lm	2700 K	94.6	93	40	748	84.1	161	1	0	2
13500 lm	3000 K	91.9	96	40	726	81.5	166	1	0	2
13500 lm	4000 K	87.6	101	40	692	77.4	174	1	0	2
15000 lm	2700 K	100	98	60	538	89.1	168	1	0	2
15000 lm	3000 K	97.2	101	60	524	86.5	173	1	0	2
15000 lm	4000 K	92.7	106	60	498	82.3	182	1	0	2
18000 lm	2700 K	124.2	95	60	656	109.9	164	2	0	2
18000 lm	3000 K	120.6	97	60	638	106.6	169	2	0	2
18000 lm	4000 K	114.6	103	60	608	101.2	178	2	0	2
21000 lm	2700 K	147.7	93	60	780	131.6	160	2	0	2
21000 lm	3000 K	143.4	96	60	756	127.6	165	2	0	2
21000 lm	4000 K	136.4	101	60	720	121.1	173	2	0	2
24000 lm	2700 K	171.4	91	60	906	154.4	155	2	0	2
24000 lm	3000 K	166.4	94	60	878	149.6	160	2	0	2
24000 lm	4000 K	158.4	99	60	836	141.8	169	2	0	2

Antares | Luminaire | Antares L

Optic: T4 medium

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	2	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	2	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	2	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	3
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	3
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	3
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: T4 medium + BLC

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	1	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	1	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	1	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	1	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	1	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	1	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	2	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	2	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	2	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	2	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	2	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	2	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	2	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	2	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	2	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	2	0	2
18000 lm	3000 K	120.6	149	60	638	106.6	169	2	0	2
18000 lm	4000 K	114.6	157	60	608	101.2	178	2	0	2
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	2
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	2
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	2
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: T5 square medium

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	2	0	0
7500 lm	2700 K	50.8	148	40	396	43.1	174	3	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	3	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	3	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	3	0	1
9000 lm	3000 K	59.6	151	40	468	51.2	176	3	0	1
9000 lm	4000 K	56.9	158	40	446	48.7	185	3	0	1
10500 lm	2700 K	72	146	40	568	62.8	167	3	0	1
10500 lm	3000 K	70.1	150	40	552	61	172	3	0	1
10500 lm	4000 K	66.8	157	40	526	57.9	181	3	0	1
12000 lm	2700 K	83.1	144	40	656	73.2	164	3	0	1
12000 lm	3000 K	80.8	149	40	638	71.1	169	3	0	1
12000 lm	4000 K	77	156	40	608	67.5	178	3	0	1
13500 lm	2700 K	94.6	143	40	748	84.1	161	3	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	3	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	3	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	4	0	2
18000 lm	3000 K	120.6	149	60	638	106.6	169	4	0	2
18000 lm	4000 K	114.6	157	60	608	101.2	178	4	0	2
21000 lm	2700 K	147.7	142	60	780	131.6	160	4	0	2
21000 lm	3000 K	143.4	146	60	756	127.6	165	4	0	2
21000 lm	4000 K	136.4	154	60	720	121.1	173	4	0	2
24000 lm	2700 K	171.4	140	60	906	154.4	155	4	0	2
24000 lm	3000 K	166.4	144	60	878	149.6	160	4	0	2
24000 lm	4000 K	158.4	152	60	836	141.8	169	4	0	2

Antares | Luminaire | Antares L

Optic: T5 Round

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	2	0	0
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	0
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	0
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	0
9000 lm	2700 K	61.2	147	40	480	52.7	171	3	0	0
9000 lm	3000 K	59.6	151	40	468	51.2	176	3	0	0
9000 lm	4000 K	56.9	158	40	446	48.7	185	3	0	0
10500 lm	2700 K	72	146	40	568	62.8	167	3	0	0
10500 lm	3000 K	70.1	150	40	552	61	172	3	0	0
10500 lm	4000 K	66.8	157	40	526	57.9	181	3	0	0
12000 lm	2700 K	83.1	144	40	656	73.2	164	3	0	1
12000 lm	3000 K	80.8	149	40	638	71.1	169	3	0	1
12000 lm	4000 K	77	156	40	608	67.5	178	3	0	1
13500 lm	2700 K	94.6	143	40	748	84.1	161	3	0	1
13500 lm	3000 K	91.9	147	40	726	81.5	166	3	0	1
13500 lm	4000 K	87.6	154	40	692	77.4	174	3	0	1
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	1
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	1
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	1
18000 lm	2700 K	124.2	145	60	656	109.9	164	4	0	1
18000 lm	3000 K	120.6	149	60	638	106.6	169	4	0	1
18000 lm	4000 K	114.6	157	60	608	101.2	178	4	0	1
21000 lm	2700 K	147.7	142	60	780	131.6	160	4	0	1
21000 lm	3000 K	143.4	146	60	756	127.6	165	4	0	1
21000 lm	4000 K	136.4	154	60	720	121.1	173	4	0	1
24000 lm	2700 K	171.4	140	60	906	154.4	155	4	0	1
24000 lm	3000 K	166.4	144	60	878	149.6	160	4	0	1
24000 lm	4000 K	158.4	152	60	836	141.8	169	4	0	1

Antares | Luminaire | Antares L

Optic: Left corner

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	3	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	3	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	3	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	3	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	3	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	3	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	3
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	3
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	3
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3

Antares | Luminaire | Antares L

Optic: Right corner

Lens: Transparent

System					Source			BUG		
Luminous Flux	Nominal CCT	W	lm/W	n° led	mA	W	lm/W	Backlight	Uplight	Glare
4000 lm	Amber	117.4	34	60	750	103.8	39	1	0	1
7500 lm	2700 K	50.8	148	40	396	43.1	174	2	0	1
7500 lm	3000 K	49.4	152	40	386	41.8	179	2	0	1
7500 lm	4000 K	47.1	159	40	368	39.8	188	2	0	1
9000 lm	2700 K	61.2	147	40	480	52.7	171	2	0	2
9000 lm	3000 K	59.6	151	40	468	51.2	176	2	0	2
9000 lm	4000 K	56.9	158	40	446	48.7	185	2	0	2
10500 lm	2700 K	72	146	40	568	62.8	167	2	0	2
10500 lm	3000 K	70.1	150	40	552	61	172	2	0	2
10500 lm	4000 K	66.8	157	40	526	57.9	181	2	0	2
12000 lm	2700 K	83.1	144	40	656	73.2	164	3	0	2
12000 lm	3000 K	80.8	149	40	638	71.1	169	3	0	2
12000 lm	4000 K	77	156	40	608	67.5	178	3	0	2
13500 lm	2700 K	94.6	143	40	748	84.1	161	3	0	2
13500 lm	3000 K	91.9	147	40	726	81.5	166	3	0	2
13500 lm	4000 K	87.6	154	40	692	77.4	174	3	0	2
15000 lm	2700 K	100	150	60	538	89.1	168	3	0	2
15000 lm	3000 K	97.2	154	60	524	86.5	173	3	0	2
15000 lm	4000 K	92.7	162	60	498	82.3	182	3	0	2
18000 lm	2700 K	124.2	145	60	656	109.9	164	3	0	3
18000 lm	3000 K	120.6	149	60	638	106.6	169	3	0	3
18000 lm	4000 K	114.6	157	60	608	101.2	178	3	0	3
21000 lm	2700 K	147.7	142	60	780	131.6	160	3	0	3
21000 lm	3000 K	143.4	146	60	756	127.6	165	3	0	3
21000 lm	4000 K	136.4	154	60	720	121.1	173	3	0	3
24000 lm	2700 K	171.4	140	60	906	154.4	155	3	0	3
24000 lm	3000 K	166.4	144	60	878	149.6	160	3	0	3
24000 lm	4000 K	158.4	152	60	836	141.8	169	3	0	3