

Nova S | Luminaire | Nova S

SOURCE

High-power LED matrix.
Standard Deviation Colour Matching ≤5

LIGHTING CHARACTERISTICS

Modular 2x2 refractive lenses in PMMA.

MECHANICAL CHARACTERISTICS

Structure made of die-cast aluminum (UNI EN 1706) with a bell-shaped upper frame equipped with a G3/4" threaded mounting tube and a skirted lower frame openable via hinge for access to the auxiliary and optical compartment.
Protective shield in extra-clear or prismatic tempered glass with IK10/IK07 impact resistance (EN 62262) and white internal reflector.
Stainless steel fastening elements, osmotic valve for pressure balancing, and compartment prepared for remote monitoring systems.

INSTALLATION

Suspended: threaded connection G3/4".


WARNINGS

Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional.
Replaceable control gear by a professional.
Protection of surfaces: please refer to the specification on painting procedures of the materials.

Nova S | Luminaire | Nova S


T1 short

Prismatic




T2 medium

Prismatic




T3 narrow

Prismatic




T3 medium

Prismatic




T4 wide

Prismatic




T4 medium

Prismatic



T5 square medium

Prismatic



Nova S | Luminaire | Nova S

Luminous Flux	Nominal CCT	W	lm/W	n° led	Optic	Screen	BUG		
2500 lm	2700 K	19.2	130	16	T4 wide	Prismatic	1	0	1
2500 lm	2700 K	19.2	130	16	T5 square medium	Prismatic	1	0	1
2500 lm	2700 K	19.2	130	16	T1 short	Prismatic	1	0	1
2500 lm	2700 K	19.2	130	16	T3 narrow	Prismatic	1	0	1
2500 lm	2700 K	19.2	130	16	T2 medium	Prismatic	1	0	1
2500 lm	2700 K	19.2	130	16	T3 medium	Prismatic	1	0	1
2500 lm	2700 K	19.2	130	16	T4 medium	Prismatic	1	0	1
2500 lm	3000 K	18.2	137	16	T4 wide	Prismatic	1	0	1
2500 lm	3000 K	18.2	137	16	T5 square medium	Prismatic	1	0	1
2500 lm	3000 K	18.2	137	16	T1 short	Prismatic	1	0	1
2500 lm	3000 K	18.2	137	16	T3 narrow	Prismatic	1	0	1
2500 lm	3000 K	18.2	137	16	T2 medium	Prismatic	1	0	1
2500 lm	3000 K	18.2	137	16	T3 medium	Prismatic	1	0	1
2500 lm	3000 K	18.2	137	16	T4 medium	Prismatic	1	0	1
2500 lm	4000 K	17.3	145	16	T4 wide	Prismatic	1	0	1
2500 lm	4000 K	17.3	145	16	T5 square medium	Prismatic	1	0	1
2500 lm	4000 K	17.3	145	16	T1 short	Prismatic	1	0	1
2500 lm	4000 K	17.3	145	16	T3 narrow	Prismatic	1	0	1
2500 lm	4000 K	17.3	145	16	T2 medium	Prismatic	1	0	1
2500 lm	4000 K	17.3	145	16	T3 medium	Prismatic	1	0	1
2500 lm	4000 K	17.3	145	16	T4 medium	Prismatic	1	0	1
3500 lm	2700 K	27.6	127	16	T4 wide	Prismatic	1	0	1
3500 lm	2700 K	27.6	127	16	T5 square medium	Prismatic	1	0	1
3500 lm	2700 K	27.6	127	16	T1 short	Prismatic	2	0	1
3500 lm	2700 K	27.6	127	16	T3 narrow	Prismatic	1	0	1
3500 lm	2700 K	27.6	127	16	T2 medium	Prismatic	1	0	1
3500 lm	2700 K	27.6	127	16	T3 medium	Prismatic	1	0	1
3500 lm	2700 K	27.6	127	16	T4 medium	Prismatic	1	0	1
3500 lm	3000 K	26.1	134	16	T4 wide	Prismatic	1	0	1
3500 lm	3000 K	26.1	134	16	T5 square medium	Prismatic	1	0	1
3500 lm	3000 K	26.1	134	16	T1 short	Prismatic	2	0	1
3500 lm	3000 K	26.1	134	16	T3 narrow	Prismatic	1	0	1
3500 lm	3000 K	26.1	134	16	T2 medium	Prismatic	1	0	1
3500 lm	3000 K	26.1	134	16	T3 medium	Prismatic	1	0	1
3500 lm	3000 K	26.1	134	16	T4 medium	Prismatic	1	0	1
3500 lm	4000 K	24.7	142	16	T4 wide	Prismatic	1	0	1
3500 lm	4000 K	24.7	142	16	T5 square medium	Prismatic	1	0	1
3500 lm	4000 K	24.7	142	16	T1 short	Prismatic	2	0	1
3500 lm	4000 K	24.7	142	16	T3 narrow	Prismatic	1	0	1
3500 lm	4000 K	24.7	142	16	T2 medium	Prismatic	1	0	1
3500 lm	4000 K	24.7	142	16	T3 medium	Prismatic	1	0	1
3500 lm	4000 K	24.7	142	16	T4 medium	Prismatic	1	0	1
4500 lm	2700 K	36.4	124	16	T4 wide	Prismatic	1	0	1
4500 lm	2700 K	36.4	124	16	T5 square medium	Prismatic	2	0	1
4500 lm	2700 K	36.4	124	16	T1 short	Prismatic	2	0	1
4500 lm	2700 K	36.4	124	16	T3 narrow	Prismatic	1	0	1
4500 lm	2700 K	36.4	124	16	T2 medium	Prismatic	1	0	1
4500 lm	2700 K	36.4	124	16	T3 medium	Prismatic	1	0	1
4500 lm	2700 K	36.4	124	16	T4 medium	Prismatic	1	0	1
4500 lm	3000 K	34.4	131	16	T4 wide	Prismatic	1	0	1
4500 lm	3000 K	34.4	131	16	T5 square medium	Prismatic	2	0	1
4500 lm	3000 K	34.4	131	16	T1 short	Prismatic	2	0	1
4500 lm	3000 K	34.4	131	16	T3 narrow	Prismatic	1	0	1
4500 lm	3000 K	34.4	131	16	T2 medium	Prismatic	1	0	1
4500 lm	3000 K	34.4	131	16	T3 medium	Prismatic	1	0	1

Nova S | Luminaire | Nova S

Luminous Flux	Nominal CCT	W	lm/W	n° led	Optic	Screen	BUG		
4500 lm	3000 K	34.4	131	16	T4 medium	Prismatic	1	0	1
4500 lm	4000 K	32.6	138	16	T4 wide	Prismatic	1	0	1
4500 lm	4000 K	32.6	138	16	T5 square medium	Prismatic	2	0	1
4500 lm	4000 K	32.6	138	16	T1 short	Prismatic	2	0	1
4500 lm	4000 K	32.6	138	16	T3 narrow	Prismatic	1	0	1
4500 lm	4000 K	32.6	138	16	T2 medium	Prismatic	1	0	1
4500 lm	4000 K	32.6	138	16	T3 medium	Prismatic	1	0	1
4500 lm	4000 K	32.6	138	16	T4 medium	Prismatic	1	0	1
6000 lm	2700 K	47.9	125	24	T4 wide	Prismatic	1	0	2
6000 lm	2700 K	47.9	125	24	T5 square medium	Prismatic	2	0	1
6000 lm	2700 K	47.9	125	24	T1 short	Prismatic	2	0	2
6000 lm	2700 K	47.9	125	24	T3 narrow	Prismatic	1	0	1
6000 lm	2700 K	47.9	125	24	T2 medium	Prismatic	1	0	1
6000 lm	2700 K	47.9	125	24	T3 medium	Prismatic	1	0	1
6000 lm	2700 K	47.9	125	24	T4 medium	Prismatic	1	0	1
6000 lm	3000 K	45.5	132	24	T4 wide	Prismatic	1	0	2
6000 lm	3000 K	45.5	132	24	T5 square medium	Prismatic	2	0	1
6000 lm	3000 K	45.5	132	24	T1 short	Prismatic	2	0	2
6000 lm	3000 K	45.5	132	24	T3 narrow	Prismatic	1	0	1
6000 lm	3000 K	45.5	132	24	T2 medium	Prismatic	1	0	1
6000 lm	3000 K	45.5	132	24	T3 medium	Prismatic	1	0	1
6000 lm	3000 K	45.5	132	24	T4 medium	Prismatic	1	0	1
6000 lm	4000 K	43	140	24	T4 wide	Prismatic	1	0	2
6000 lm	4000 K	43	140	24	T5 square medium	Prismatic	2	0	1
6000 lm	4000 K	43	140	24	T1 short	Prismatic	2	0	2
6000 lm	4000 K	43	140	24	T3 narrow	Prismatic	1	0	1
6000 lm	4000 K	43	140	24	T2 medium	Prismatic	1	0	1
6000 lm	4000 K	43	140	24	T3 medium	Prismatic	1	0	1
6000 lm	4000 K	43	140	24	T4 medium	Prismatic	1	0	1
7500 lm	2700 K	61.1	123	24	T4 wide	Prismatic	2	0	2
7500 lm	2700 K	61.1	123	24	T5 square medium	Prismatic	3	0	1
7500 lm	2700 K	61.1	123	24	T1 short	Prismatic	2	0	2
7500 lm	2700 K	61.1	123	24	T3 narrow	Prismatic	2	0	1
7500 lm	2700 K	61.1	123	24	T2 medium	Prismatic	2	0	1
7500 lm	2700 K	61.1	123	24	T3 medium	Prismatic	2	0	2
7500 lm	2700 K	61.1	123	24	T4 medium	Prismatic	2	0	2
7500 lm	3000 K	57.8	130	24	T4 wide	Prismatic	2	0	2
7500 lm	3000 K	57.8	130	24	T5 square medium	Prismatic	3	0	1
7500 lm	3000 K	57.8	130	24	T1 short	Prismatic	2	0	2
7500 lm	3000 K	57.8	130	24	T3 narrow	Prismatic	2	0	1
7500 lm	3000 K	57.8	130	24	T2 medium	Prismatic	2	0	1
7500 lm	3000 K	57.8	130	24	T3 medium	Prismatic	2	0	2
7500 lm	3000 K	57.8	130	24	T4 medium	Prismatic	2	0	2
7500 lm	4000 K	54.7	137	24	T4 wide	Prismatic	2	0	2
7500 lm	4000 K	54.7	137	24	T5 square medium	Prismatic	3	0	1
7500 lm	4000 K	54.7	137	24	T1 short	Prismatic	2	0	2
7500 lm	4000 K	54.7	137	24	T3 narrow	Prismatic	2	0	1
7500 lm	4000 K	54.7	137	24	T2 medium	Prismatic	2	0	1
7500 lm	4000 K	54.7	137	24	T3 medium	Prismatic	2	0	2
7500 lm	4000 K	54.7	137	24	T4 medium	Prismatic	2	0	2
9000 lm	2700 K	71.1	127	32	T4 wide	Prismatic	2	0	2
9000 lm	2700 K	71.1	127	32	T5 square medium	Prismatic	3	0	1
9000 lm	2700 K	71.1	127	32	T1 short	Prismatic	3	0	2
9000 lm	2700 K	71.1	127	32	T3 narrow	Prismatic	2	0	1
9000 lm	2700 K	71.1	127	32	T2 medium	Prismatic	2	0	2

Nova S | Luminaire | Nova S

Luminous Flux	Nominal CCT	W	lm/W	n° led	Optic	Screen	BUG		
9000 lm	2700 K	71.1	127	32	T3 medium	Prismatic	2	0	2
9000 lm	2700 K	71.1	127	32	T4 medium	Prismatic	2	0	2
9000 lm	3000 K	67.4	134	32	T4 wide	Prismatic	2	0	2
9000 lm	3000 K	67.4	134	32	T5 square medium	Prismatic	3	0	1
9000 lm	3000 K	67.4	134	32	T1 short	Prismatic	3	0	2
9000 lm	3000 K	67.4	134	32	T3 narrow	Prismatic	2	0	1
9000 lm	3000 K	67.4	134	32	T2 medium	Prismatic	2	0	2
9000 lm	3000 K	67.4	134	32	T3 medium	Prismatic	2	0	2
9000 lm	3000 K	67.4	134	32	T4 medium	Prismatic	2	0	2
9000 lm	4000 K	63.9	141	32	T4 wide	Prismatic	2	0	2
9000 lm	4000 K	63.9	141	32	T5 square medium	Prismatic	3	0	1
9000 lm	4000 K	63.9	141	32	T1 short	Prismatic	3	0	2
9000 lm	4000 K	63.9	141	32	T3 narrow	Prismatic	2	0	1
9000 lm	4000 K	63.9	141	32	T2 medium	Prismatic	2	0	2
9000 lm	4000 K	63.9	141	32	T3 medium	Prismatic	2	0	2
9000 lm	4000 K	63.9	141	32	T4 medium	Prismatic	2	0	2
10500 lm	2700 K	84.2	125	32	T4 wide	Prismatic	2	0	2
10500 lm	2700 K	84.2	125	32	T5 square medium	Prismatic	3	0	1
10500 lm	2700 K	84.2	125	32	T1 short	Prismatic	3	0	3
10500 lm	2700 K	84.2	125	32	T3 narrow	Prismatic	2	0	2
10500 lm	2700 K	84.2	125	32	T2 medium	Prismatic	2	0	2
10500 lm	2700 K	84.2	125	32	T3 medium	Prismatic	2	0	2
10500 lm	2700 K	84.2	125	32	T4 medium	Prismatic	2	0	2
10500 lm	3000 K	79.7	132	32	T4 wide	Prismatic	2	0	2
10500 lm	3000 K	79.7	132	32	T5 square medium	Prismatic	3	0	1
10500 lm	3000 K	79.7	132	32	T1 short	Prismatic	3	0	3
10500 lm	3000 K	79.7	132	32	T3 narrow	Prismatic	2	0	2
10500 lm	3000 K	79.7	132	32	T2 medium	Prismatic	2	0	2
10500 lm	3000 K	79.7	132	32	T3 medium	Prismatic	2	0	2
10500 lm	3000 K	79.7	132	32	T4 medium	Prismatic	2	0	2
10500 lm	4000 K	75.4	139	32	T4 wide	Prismatic	2	0	2
10500 lm	4000 K	75.4	139	32	T5 square medium	Prismatic	3	0	1
10500 lm	4000 K	75.4	139	32	T1 short	Prismatic	3	0	3
10500 lm	4000 K	75.4	139	32	T3 narrow	Prismatic	2	0	2
10500 lm	4000 K	75.4	139	32	T2 medium	Prismatic	2	0	2
10500 lm	4000 K	75.4	139	32	T3 medium	Prismatic	2	0	2
10500 lm	4000 K	75.4	139	32	T4 medium	Prismatic	2	0	2
12000 lm	3000 K	86.7	138	48	T4 wide	Prismatic	2	0	3
12000 lm	3000 K	86.7	138	48	T5 square medium	Prismatic	3	0	2
12000 lm	3000 K	86.7	138	48	T1 short	Prismatic	3	0	3
12000 lm	3000 K	86.7	138	48	T3 narrow	Prismatic	2	0	2
12000 lm	3000 K	86.7	138	48	T2 medium	Prismatic	2	0	2
12000 lm	3000 K	86.7	138	48	T3 medium	Prismatic	2	0	2
12000 lm	3000 K	86.7	138	48	T4 medium	Prismatic	2	0	2
12000 lm	4000 K	82.1	146	48	T4 wide	Prismatic	2	0	3
12000 lm	4000 K	82.1	146	48	T5 square medium	Prismatic	3	0	2
12000 lm	4000 K	82.1	146	48	T1 short	Prismatic	3	0	3
12000 lm	4000 K	82.1	146	48	T3 narrow	Prismatic	2	0	2
12000 lm	4000 K	82.1	146	48	T2 medium	Prismatic	2	0	2
12000 lm	4000 K	82.1	146	48	T3 medium	Prismatic	2	0	2
12000 lm	4000 K	82.1	146	48	T4 medium	Prismatic	2	0	2