

Project location:

Project name:

Fixture type:Qty:

Notes:

Nebula Pathlight | Luminaire | 1 light

Ordering Information / Guide

Example: **PLNEB01-N-D00-830-L005-SS-V1-F06-M2-CN0**

Optique	Ra+K	Luminous flux	Screen finish	Power supply	Driver Function	ISO Class	Finish
D00 Diffuse	830 Ra80 3000 K	L002 200 lm	SS Smoky grey	V0 120V-277V	F06 DALI+CLO	M1 Class I	CN0 Grey [Neri] Textured
	8CW Ra80 RGBW	L005 450 lm		V1 220V-240V	F30 DMX	M2 Class II	

Generated code: **PLNEB01 - N** - \_ \_ \_ \_ \_ - \_ \_ \_ \_ \_ - \_ \_ \_ \_ \_ - \_ \_ \_ \_ \_

## Nebula Pathlight | Luminaire | 1 light

### ELECTRICAL CHARACTERISTICS

Compliant with standards EN 60598-1; EN 60598-2-3; EN 62031; EN 55015  
EMC; EN 61547 EMC; EN 61000-3-2/3; IEC/TR 62778.

### WARNINGS

Luminaire designed for disposal/recycling at end-of-life.

Replaceable (LED only) light source by a professional.


Replaceable control gear by a professional.

Protection of surfaces: please refer to the specification on painting  
procedures of the materials.

Nebula Pathlight | Luminaire | 1 light

Diffuse

Smoky grey



Project location:

Project name:

Fixture type:Qty:

Notes:

Nebula Pathlight | Luminaire | 1 light

Luminous Flux	Nominal CCT	W	lm/W	n° led	Optic	Screen	BUG		
500 lm	3000 K	12	42	1	Diffuse	Smoky grey	0	3	1