

Project location:

Project name:

Fixture type:Qty:

Notes:

Nebula Pathlight | Luminaire | 2 lights

Ordering Information / Guide

Example: **PLNEB02-N-D00-830-L010-SS-V1-F06-M2-CN0**

| Optique | Ra+K | Luminous flux | Screen finish | Power supply | Driver Function | ISO Class | Finish |
|----------------|--------------------|-----------------|------------------|-----------------|-----------------|----------------|-----------------------------|
| D00 Diffuse | 830 Ra80 3000 K | L004 350 lm | SS Smoky grey | V0 120V-277V | F06 DALI+CLO | M1 Class I | CN0 Grey [Neri] Textured |
| | 8CW Ra80 RGBW | L010 1000 lm | | V1 220V-240V | F30 DMX | M2 Class II | |

Generated code: **PLNEB02 - N** - _

Nebula Pathlight | Luminaire | 2 lights

ELECTRICAL CHARACTERISTICS

Compliant with standards EN 60598-1; EN 60598-2-3; EN 62031; EN 55015
EMC; EN 61547 EMC; EN 61000-3-2/3; IEC/TR 62778.


WARNINGS

Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional.
Replaceable control gear by a professional.
Protection of surfaces: please refer to the specification on painting
procedures of the materials.

Nebula Pathlight | Luminaire | 2 lights

Diffuse

Smoky grey



Project location:

Project name:

Fixture type:Qty:

Notes:

Nebula Pathlight | Luminaire | 2 lights

| Luminous Flux | Nominal CCT | W | lm/W | n° led | Optic | Screen | BUG | | |
|---------------|-------------|----|------|--------|---------|------------|-----|---|---|
| 1000 lm | 3000 K | 24 | 42 | 2 | Diffuse | Smoky grey | 0 | 3 | 1 |