

# NERI

Light 20 (serie 201)  
Light source: discharge lamps

Serie **SN201** + SSS X YY ZZ  
Mounting:suspended

Technical sheet  
Rev. A 11-2015  
Measures in mm

## DESCRIPTION

### Dimensions - Area exposed to wind pressure - Weight

Height	Width	Lenght	Diameter	Area esposed to wind (S)	Weight
640 mm			450 mm	0.198 m <sup>2</sup>	8.7 Kg

### Electrical characteristics (electromagnetic wiring)

Voltage	Frequency	IP	Insulation class	Cos $\Phi$	Oper. Temp. °C
230V	50Hz	66	CL II $\square$ CL I $\pm$ (on request)	> 0.9	-30... +40

### Conformity

	2014/35/UE (LVD)	2014/30/UE (EMC)	2011/65/UE (RoHS)	(ErP)
--	---------------------	---------------------	----------------------	-------

### Mounting system

- Suitable for suspended mounting.
- Connection with threaded tube male G 3/4" with cable gland (PG16) inside.

### Materials

- Die-cast and sheet aluminum (UNI EN 1706).
- Acrylic screen (PMMA).
- Screws in stainless steel and brass.

### Structure - Main components

- Upper frame composed by a bell in die-cast aluminum, equipped with a threaded tube G3/4" for mounting to the support arm.
- Lower frame for access to optical and wiring compartment, composed by a ring in die-cast aluminum for the support of screen, equipped of two small knobs for opening.
- Wiring plate in aluminum sheet painted white colour, easily removable.
- Neoprene gasket between upper and lower frame.
- Skirt-shaped screen in acrylic (PMMA) white frosted finish. Shock resistance IK06.

### Optics

- Reflector mod. 1 - street and mixed areas ighting - Installation on the side of street.


### Operations and maintenance

- To opening the light fixture and access to wiring and optic compartment, loosen the two small knobs on cover and remove the lower frame with screen.
- To remove the wiring plate, loosen the screws and rotate the plate.
- Separate electric auxiliaries individually replaceable.
- During installation follow the instructions for the correct optic orientation on the support.
- Periodic maintenance (about once a year) for external cleaning of the structure and screen from dust and smog, and the control of fastening of all screws, must be performed with light fixture switched off and cold.


### Painting

- Standard color is metalized matt dark gray, type Neri.
- Other colours of RAL range on request.
- Information about paint steps used on this product in specific technical sheet.

## DRAWINGS AND TECHNICAL INFORMATIONS



Side view



Plan view



## Code construction

To configure the complete code of luminaire, add in sequence after **Serie** code, the others parts of code: Ballast-screen (**SSS**) + Optic (**X**) + Lamp predisposition (**YY**) + Wiring type (**ZZ**). See configurations tables on the following page.

**Property of Neri S.p.A.** - Any use and reproduction for personal purposes is prohibited. Company shall reserve the right at any time to modify the specification or features without notice.

## CONFIGURATION WITH ELECTROMAGNETIC WIRINGS

### Screens

Cod. SSS	Light fixture series	Materials	Finiture	Shock R.
A12	201-301	Acrylic (PMMA)	White frosted	IK06

### Optics

Cod. X	Type	Lighting classes	Classe IES
1	mod. 1 - Fixed	Street lighting.	Cut-off

- Reflector mod. 1 in pressed sheet aluminum (thickness 1 mm, purity 99.90%), polished and oxidized.
- Height of installation: from 3.5 to 6.5 meters.

### Wirings (Predisposition for lamps with optical and socket)

Cod. YY	Lamps predisposition	W	Optics	Sockets
32	(MT) Metal halide - (ST) Sodium H.P.	70	1	E27
33	(MT) Metal halide - (ST) Sodium H.P.	100	1	E40
35	(MT) Metal halide - (ST) Sodium H.P.	150	1	E40

- Electromagnetic ballast with high efficiency (CELMA class EEI=A3), with thermal protection.
- Electronic ignitor (pulses until to 4.5 KV).
- Power factor correction capacitor.
- Ceramic lamp holders in relation to the type of lamp.
- Electric components on wiring plate easily removable.
- Terminal board for cables with max section of 2,5 mm<sup>2</sup>.

### Wirings (Characteristics)

Cod. ZZ	Details
04	Insulation class CL II  - Fuse 250V-T6.3A (5 x 20 mm)

### Note

- Use lamps with efficiency  $\geq$  di 90 lm/W.
- The lamps are not included in the wiring.
- On request can be realized other wiring configurations.

## PHOTOMETRICS OF REFERENCE

**Reflector mod. 1** - Screen skirt-shaped in acrylic white frosted.  
Asymmetric for street lighting - Cut off - Type III

