



Ref. Certif. No.

DK-86121-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)  
CB SCHEME

## CB TEST CERTIFICATE

Product

Luminaire for road and street lighting

Name and address of the applicant

NERI SPA  
SS EMILIA 1622  
LONGIANO, 47020 FC Italy

Name and address of the manufacturer

NERI SPA  
SS EMILIA 1622  
LONGIANO, 47020 FC Italy

Name and address of the factory

Note: When more than one factory, please report on page 2

NERI SPA  
Via Delle Querce 4  
Longiano, 47020 Fc Italy☐ Additional Information on page 2

Ratings and principal characteristics

220-240 V ~ 50/60 Hz 160 W Class II IP65 IK09 ta 50°C  
See Page 2

Trademark (if any)

NERI

Type of Customer's Testing Facility (CTF) Stage used

CTF Stage 2

Model / Type Ref.

Light Matar 32+32  
See Page 2

Additional information (if necessary may also be reported on page 2)

☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60598-1:2014/ AMD1:2017, IEC 60598-1:2014, IEC 60598-2-3:2002/AMD1:2011, IEC 60598-2-3:2002

As shown in the Test Report Ref. No. which forms part of this Certificate

4788598740 issued on 2019-07-19

This CB Test Certificate is issued by the National Certification Body



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2019-07-26

Signature:

Jan-Erik Storgaard



Ref. Certif. No.

DK-86121-UL

Model details:

**Variants:**

The main model extends series Light Matar:

Type ref.	Ratings
Light Matar 32+32	220-240 V ~ 50/60 Hz 160 W Class II IP65 IK09 $t_a$ 50°C

extends the models:

Type ref.	Ratings
Light Matar 24+24	220-240 V ~ 50/60 Hz 140 W Class II IP65 IK09 $t_a$ 50°C
Light Matar 16+16	220-240 V ~ 50/60 Hz 80 W Class II IP65 IK09 $t_a$ 50°C

Each model has other variants which are internally identified, related to customers features and not affecting safety but the correlated temperature color of the light source limited up to 4000K.

**Additional Information:**

Additionally evaluated to EN 60598-2-3:2003/ A1:2011 and EN 60598-1:2015/ A1:2018

National Differences specified in the CB Test Report

**Additional information (if necessary)**

UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2019-07-26

Signature:

Jan-Erik Storgaard