






# TEST REPORT

## No. AI19-0046170-03

### SURGE IMMUNITY TEST

performed in accordance with

- ☒ IEC 61000-4-5:2014 + A1:2017  
☒ EN 61000-4-5:2014 + A1:2017  
☐ CEI EN 61000-4-5:2015 + A1:2018

PRODUCT	LED Luminaire
MODEL TESTED	Art. Matar 24+24
SERIES	<b>NERI</b> Matar 24+24 <b>Made in Italy</b> MNMATL203R806 Ratings: 220-240V~ 50/60Hz 127W IP65 IK09 Ta +50°C -35°C Conf: DALI+NCL Light output: 15000lm 4000K Optic: Type II-A Source: 24+24 LED 740   
TRADE MARK	Batch: Date: 12/20 Serial: 00001  <b>Neri S.p.A.</b> Via Emilia, 1622 47020 Longiano (FC) Italy  000001 
APPLICANT	NERI S.p.A. Via Emilia, 1622 - 47020 Longiano (FC) - Italy

Tested by	Giordano Carcano [Laboratory technician]	
Approved by	Giovanni Di Turi [Laboratory manager]	

### Revision Sheet

Release No.	Date	Revision Description
Rev. 0	2020-04-01	First edition






## 1. GENERAL DATA

SAMPLE		
Samples received on	2019-11- 29 / 2020-01-03	(item sent and sampling by applicant)
IMQ reference samples	BEM	97978 / 98323
Samples tested No.	1	
Object under analysis recognition	Not carried out	
Remark:	Except where stated, characteristics of products were taken from client description and were not verified by the laboratory	
Date of acceptance of test item	2020-01-14	
TEST LOCATION		
Testing dates	2020-01-14 ÷ 2020-01-15	
Testing laboratory	IMQ S.p.A. - Via Quintiliano, 43 – IT - 20138 Milano	
Testing site	Via Quintiliano, 43 – I - 20138 Milano	
ENVIRONMENTAL CONDITIONS		
Parameter	Range	
Ambient Temperature	20 ÷ 25 °C	
Relative Humidity	50 ÷ 60 %	
Atmospheric Pressure	900 ÷ 1000 mbar	
The laboratory is monitored by a continuous environmental conditions measurements system. Temperature, humidity and pressure data are recorded on a weekly basis and stored in local archive.		

## 2. REFERENCE DOCUMENT

	DOCUMENT	DATE	TITLE
<input checked="" type="checkbox"/>	IEC 61000-4-5 A1	2014 2017	Electromagnetic Compatibility (EMC) Part 4-5: Testing and measurement techniques Surge immunity test
<input checked="" type="checkbox"/>	EN 61000-4-5 A1	2014 2017	Electromagnetic Compatibility (EMC) Part 4-5: Testing and measurement techniques Surge immunity test
<input type="checkbox"/>	CEI EN 61000-4-5 A1	2015 2018	Electromagnetic Compatibility (EMC) Part 4-5: Testing and measurement techniques Surge immunity test

### 3. EQUIPMENT UNDER TEST (EUT) DETAILS

Label	
<p><b>NERI</b> Matar 24+24</p> <p>Made in Italy MNMATL203R806</p> <p>Ratings: 220-240V~ 50/60Hz 127W</p> <p>IP65 IK09 Ta +50°C -35°C Conf: DALI+NCL</p> <p>Light output: 15000lm 4000K Optic: Type II-A</p> <p>Source: 24+24 LED 740</p> <p>Neri S.p.A. Via Emilia, 1622 47020 Longiano (FC) Italy</p>	<p>Batch: Date: 12/20 Serial: 00001</p> <p>   </p> <p> 000001</p>

MODEL (basic)	Description						
Art. Matar 24+24	LED street lighting equipment 220-240V 127W						
	<table><tr><th>Light source</th><th>LED</th><th>Electronic controlgear for led module</th></tr><tr><td>LECCE</td><td>24+24 x Nichia NVSW219F</td><td>Philips Xi FP 150W 0.3-1.0A SNLDAE 230V S240 sXt</td></tr></table>	Light source	LED	Electronic controlgear for led module	LECCE	24+24 x Nichia NVSW219F	Philips Xi FP 150W 0.3-1.0A SNLDAE 230V S240 sXt
	Light source	LED	Electronic controlgear for led module				
	LECCE	24+24 x Nichia NVSW219F	Philips Xi FP 150W 0.3-1.0A SNLDAE 230V S240 sXt				
Model MNMATL203R806 represent also Matar models:							
MNMATL xx y Rn zz, where lower case letters specify photometric distribution ("xx"), CCT ("y"), light flux ("Rn"), configuration of energy saving driver functions ("zz")							

MANUFACTURER	NERI S.p.A.
ASSEMBLY PLANT	Via Emilia, 1622 - 47020 Longiano (FC) - Italy

**EUT IDENTIFICATION**

<b>EUT type</b>	Lighting equipment appliance
<b>EUT description</b>	Led luminaire for road and street lighting
<b>EUT classification</b>	Insulation class II
<b>EUT standing</b>	Fixed (suspended)
<b>EUT single or system</b>	Single

**EUT TECHNICAL DATA**

Parameters	Value
<b>Supply Voltage IN</b>	220-240V ac
<b>Supply Voltage OUT</b>	/
<b>Frequency</b>	50/60Hz
<b>Power</b>	127W
<b>Ambient rating</b>	/

**EUT CONFIGURATION**

The following peripheral devices and interface cables were connected during the measurement: none

Port	Name	Type (*)	Cable max. >3m	Cable Shielded	Comments
0	Enclosure	N/E	—	—	None
1	AC Mains	AC	Yes	No	None
2	DC Mains	DC	—	—	None
3	Load	LP	—	—	None
4	Control	CP	---	---	None
(*) <b>Note:</b> AC = AC Power Port DC = DC Power Port N/E = Non-Electrical LP = Load ports (Not Involved in Process Control) CP = Control Ports					

**MODE OF OPERATION DURING THE TESTS**

Ref.	Mode	Description
<input checked="" type="checkbox"/> #1	Normal operation	LEDs ON at maximum power

## 4. PERFORMANCE CRITERIA

### Immunity performance criteria

The test results is classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance level defined by the manufacturer or the requestor of the test, or agreed between the manufacturer and the purchaser of the product.

- A. normal performance within limits specified by the manufacturer, requestor or purchaser;
- B. temporary loss of function or degradation of performance which ceases after the disturbance ceases, and from which the equipment under test recovers its normal performance, without operator intervention;
- C. temporary loss of function or degradation of performance, the correction of which requires operator intervention;
- D. loss of function or degradation of performance which is not recoverable, owing to damage to hardware or software, or loss of data.

### EUT PERFORMANCE ASSESSMENT

As declared by manufacturer:

<b>Primary function</b>	The EUT is a LED lighting equipment
<b>Representative parameter</b>	The EUT shall continue to perform as intended
<b>Acceptable level of performance</b>	As standard requirements

## 5. SUMMARY OF TEST RESULTS

POSSIBLE TEST CASE VERDICTS:	
Test object does meet the requirement	PASS
Test object does not meet the requirement	FAIL

PORT	ENVIRONMENTAL PHENOMENON	RESULT
AC mains	Surge immunity test	PASS

## 6. RESULTS

### SURGE IMMUNITY TEST

TEST REQUIREMENT	
Reference standard	IEC 61000-4-5
Test set-up	§ 7
IMQ operational instruction	FL-EM80-I08 + FL-EM80-I11
Test procedure	IEC 61000-4-5 § 8.2
Deviation to test procedure	None
EUT operating condition	#1, during the test the EUT enclosure was connected to PE (Protective Earth), to simulate the real installation.

Port under test	Mode	Test voltage (kV)	Repetition rate	Phase angle	Polarity		Perf. criteria	Results
					+	-		
AC mains	<input checked="" type="checkbox"/> Common L-PE and N-PE	10	1 per minute (5 pulses)	90°	x		A	PASS
				270°		x		
	<input checked="" type="checkbox"/> Differential N-L	10	1 per minute (5 pulses)	90°	x		A	PASS
				270°		x		

#### REMARKS

The tested sample continues to operate as intended during and after the test.



## 7. MEASUREMENTS AND TESTS UNCERTAINTY

Unless otherwise stated the uncertainties for the tests and measurements are evaluated in accordance with IMQ Operational Instruction IO-LAB-001, IO-LAB-004 and IO-LAB-009.

The uncertainty evaluation has been carried out in accordance with IEC Guide 115 “Application of Uncertainty of measurement’s to Conformity Assessment Activity in the Electrotechnical Sector” and IECCE OD-5014.

The expanded uncertainty was calculated for all measurements and tests listed in this test report according to CISPR 16-4-2 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainty in EMC Measurements”, with UKAS document LAB 34 and is documented in the quality system accordance to ISO/IEC 17025.

Internal Procedure PG-037 ensures that the requirements for traceability of calibrations, of all test equipment requiring calibration, and calibration intervals are met.

All instrumentation used for immunity tests is calibrated and within the specifications required by the basic standards (IEC 61000-4-X).

## 8. MEASUREMENT EQUIPMENT AND INSTRUMENTATION

Test equipment used					
Description	Manufacturer	Model	Identifier	Last Calibration date	Calibration due date
SURGE generator	EMC PARTNER	MIG 1206-1P	S07044	2019-10-08	2020-10-31

## 9. PHOTOGRAPHIC DOCUMENTATION

Test set-up photo



**END OF TEST REPORT**