

## Use

Suitable support for suspended light fixtures.

## Materials

Made in UNI EN 1561 cast iron, UNI EN 1563 nodular cast iron and S235J UNI EN 10219-1 steel, hot dip galvanized according to UNI EN ISO 1461. Screws in stainless steel.

## Description

The top section is made up of the following elements:



- 1°) A hot-galvanized steel tube height 158 cm (diam. 6 cm) for the coupling on the posts with 8.9 cm of diameter; it is provided of a flange (A - diam. 7.5 cm) and a hole (diam. 2 cm) for the passage of power supply cable.
- 2°) Cast iron junction cast in a single piece, height 6.0 cm.
- 3°) A ring in hot-galvanized steel for lower support of the suspension brackets. It is secured to the supporting tube (1°) with two M8 grubs.
- 4°) A ring in hot-galvanized steel for upper support of the suspension brackets. The ring has four holes (B - Ø 1.8 cm) for the passage of power supply cable. It is secured to the supporting tube (1°) with two M8 grubs.
- 5°) Two suspension brackets, each height 106 cm with a protrusion of 75 cm. Structurally each bracket is composed of a tube in steel (diam. 4.2 cm.), decorations (E, F) in cast iron and support attachments (C) in spheroidal cast iron. The brackets are arranged at 180° to each other and fixed to the support rings 3°- 4° with four M8 screws and has at his end an internal thread G3/4" for attaching the light fixture (D). The power cables pass inside the suspension bracket (G). The entire assembly is hot-galvanized.
- 6°) A terminal element in cast iron height 26 cm fixed onto element (1°) and is secured with three M6 screws..

## Dimensions - Weight

Height cm 150  
Width cm 75  
Weight Kg 47

## Protection surfaces

Please refer to the specification on painting procedures of the materials.



**NB:** The measurements are in millimeters.

**Neri S.p.A. Property** - Any reproduction and use for its own purposes is forbidden.