

### Description

Wall bracket in UNI EN 1563 nodular cast iron and FE 360 UNI EN 10219-1 steel, hot-galvanized to UNI EN ISO 1461 corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The wall bracket is composed as follows:

- 1°) Two steel lugs for cementing into the wall, electrolytically cold-galvanized to UNI ISO 2081 standards, length 14 cm. Each lug is fitted with two M12 studs with relative blind nuts in stainless steel.
- 2°) A curved bracket with a main section composed of a steel tube (diam. 4.2 cm). The support junctions (A) are each made individually in a single casting of nodular cast iron, and have a distance between centres of 55 cm. They each project for 23 cm, and have a circular support surface at the rear with a diameter of 14 cm. The two junctions support the main tube with decorations in the form of two scotias with a torus between them and a small sphere at the outer extremity. The lower extremity of the steel tube terminates in an oval knob (a). The bracket is fixed to the lugs with four M12 stainless steel bolts, and the outer extremity (D – diam. 9 cm), also in cast iron, is provided with a 3/4" GAS thread for attaching the light fixture, a slot (B) for leading a 1.4 cm diameter power cable into the tube (diam. 4.2 cm), and an earthing terminal (C).

The total height of the wall bracket is 126 cm, with an effective projection of 81 cm.

### Protection of surfaces

Please refer to the specification on painting procedures of the materials.

