

### Description

Wall bracket in UNI EN 1561 cast iron, FE 360 UNI EN 10219-1 steel, hot-galvanized to UNI EN ISO 1461 standards, corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The wall bracket is composed as follows:

- 1°) A steel support tube (diam. 3.3 cm, length 75 cm) hot-galvanized. At the outer extremity the tube has a junction (D) welded to the support tube for attaching the light fixture, consisting in a ring that is tapered externally. Externally this junction has a 3/4" GAS thread for attaching the light fixture. The underside of junction is composed by an element (E) decorated with a torus, a moulding and a sphere. The support tube has a slot (C) for leading a 1.4 cm diameter power cable into the interior, and an earthing terminal (B).
- 2°) A cast iron bracket cast as a single piece, height 45 cm and projection 65 cm. The bracket and the support tube are joined by two collars (F), each decorated with two flutes and cast together with the bracket. The bracket is decorated as shown in the diagram. Ornamentation consists in a plate (A – height 45 cm, width 13 cm) provided with three holes (diam. 1.3 cm) for fixing to the wall with expansion bolts, three branches terminating in spirals (a, b, c), a large central flower (d), two fruit motifs, one facing downwards (e) and one upwards (f), six small curled leaves (g, h, i, l, m, n) and a large leaf extending from the centre towards the wall (o).

The total height of the wall bracket is 45 cm, with an effective projection of 75 cm.

### Protection of surfaces

Please refer to the specification on painting procedures of the materials.

