

Project location:			
Project name:			
Model #:	1161.051	Date	

DESCRIPTION


Compliance:
- Compliant with AASHTO 2015 standard.
- Design for wind speed 180 MPH.
* design criteria: 2020 Florida Building Code, Risk Category II, Exposure.

Description
Lamp post composed of elements in UNI EN 1561 cast iron with core in S355J UNI EN 10219-1 steel, hot-galvanized to UNI EN ISO 1461 standards, corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.
The core (A) is made up of five tubes of different cross-sections, according to the internal diameter of the cast iron elements (diam. cm 4 2/4" x 3' 9 1/4" diam. 3 2/4" x 13 3/4" - diam. 2 3/4" x 3' 1 3/4" - diam. 2 1/4" x 30" - diam. 2" x 34 3/4"), welded together at their junctions.
It is suitable for flange fixing (diam. 9 3/4" - thickness 2/4") on a foundation plinth (P). It is provided with an M10 earthing bolt marked by a small indicator plate, a slot (D - height 5 1/4" x 1 2/4") for the installation of a Class II insulation terminal board with or without fuse (Conchiglia), a slot (E - height 6" x 1 2/4") above ground level and an M 36 threaded bush (Z) welded to the top.
The cast iron post is made up of a number of elements that are fitted over each other so as to prevent water infiltration.
The elements are as follows:
1°) Base element height 3' 2", with a square plinth (15" x 15" x 5") with cut-off corners, surmounted by a decorative band of twenty-eight ovoli and leaf designs (F), a central section with a square cross-section with cut-off corners (9 2/4" x 9 2/4" x 24 2/4") and an inspection hatch (3 2/4" x 14 1/4"), and a square cymatium (14 1/4" x 14 1/4") with cut-off corners.
2°) Second element height 8 3/4", with a square plinth (10 3/4" x 10 3/4") with cut-off corners, decorated with a scotia (G, diam. 5 3/4") with sixteen flutes surmounted by a torus with eight ovoli (H, diam. 9 3/4").
3°) Third element height 14 1/4" (lower diam. 7" cm, central diam. 7" cm, top diam. 6") decorated with leaves.
4°) Fourth element height 3' 1/4", tapered (lower diam. 4 1/4", top diam. 3 3/4") and decorated with eight flutes.
The above elements are all cast as single pieces.

The total height of these first four elements is 8' 2/4".

Protection of surfaces
Please refer to the specification on painting procedures of the materials.

Flange detail



DRAWINGS

