

## DESCRIPTION

### Dimensions - Area exposed to wind pressure - Weight

Height	Width	Length	Diameter	Area exposed to wind (S)	Weight
820 mm			390 mm	0,184 m <sup>2</sup>	8.0 Kg

### Electrical characteristics (electromagnetic wiring)

Voltage	Frequency	IP	Insulation class	Cos $\Phi$	Oper. Temp. °C
230V	50Hz	23	CL I $\underline{\text{I}}$	> 0.9	-30... +40

### Conformity

CE	2014/35/UE (LVD)	2014/30/UE (EMC)	2011/65/UE (RoHS)	(ErP)
----	---------------------	---------------------	----------------------	-------

### Mounting system

- Suitable for suspended mounting.
- Connection with threaded tube male G 3/4" in galvanized steel.

### Materials

- Sheet in aluminum.
- Cast aluminum (UNI EN 1706).
- Galvanized steel.
- Acrylic screen (PMMA).
- Polyethylene.
- Stainless steel screws.

### Structure - Main components

- Upper frame with circular shaped richly decorated in cast and sheet aluminum equipped with a threaded tube G3/4" for connected to support. The frame is removable, loosening three screws.
- Lower frame composed by an upper circular ring, three linear vertical arms, a lower ring and a terminal element with three-arms richly decorated.
- Wiring plate in polyethylene, easily removable.
- Reflector convex shaped in sheet aluminum, white color.
- Three screens in acrylic (PMMA) transparent or frosted. Shock resistance IK06.

### Optics

- Reflector mod. 0 (reflector white painted) for mixed area lighting.
- Rotosymmetric geometry.


### Operations and maintenance

- To opening the light fixture and access to wiring and optic compartment, loosen the three lateral screws and remove the lower frame.
- To replace the lamp, remove the reflector.
- During installation, follow the instructions for the correct optic orientation on the support.
- Periodic maintenance (about once a year) for external cleaning of the structure and screen from dust and smog, and the control of fastening of all screws, must be performed with light fixture switched off and cold.


### Painting

- Standard color is metalized matt dark gray, type Neri.
- Other colours of RAL range on request.
- Information about paint steps used on this product in specific technical sheet.

## DRAWINGS AND TECHNICAL INFORMATIONS



Front view



Plan view



Example with transparent screen

## Code construction

To configure the complete code of luminaire, add in sequence after **Serie** code, the others parts of code: Ballast-screen (**SSS**) + Optic (**X**) + Lamp predisposition (**YY**) + Wiring type (**ZZ**). See configurations tables on the following page.

## CONFIGURATION WITH ELECTROMAGNETIC WIRINGS

### Screens

Cod. SSS	Light fixture series	Materials	Finiture	Shock R.
A09	650	Acrylic (PMMA)	Frosted	IK06
A11	650	Acrylic (PMMA)	Trasparent	IK06

### Optics

Cod. X	Type	Lighting classes	Classe IES
0	mod.0	Mixed area lighting - rotosymmetric	No cut-off

- Reflector in sheet aluminum white color, slightly convex with lamp in view in vertical position.
- Height of installation: from 3.5 to 4.5 meters.

### Wirings (Predisposition for lamps with optical and socket)

Cod. YY	Lamps predisposition	W	Optics	Sockets
30	(ST - SE) Sodium H.P.	50	0	E27
32	(MT-ME) Metal halide - (ST-SE) Sodium H.P.	70	0	E27
33	(MT-ME) Metal halide - (ST-SE) Sodium H.P.	100	0	E40

- Electromagnetic ballast with high efficiency (CELMA class EEI=A3 ), with thermal protection .
- Electronic ignitor (pulses until to 4.5 KV).
- Power factor correction capacitor.
- Ceramic lamp holders in relation to the type of lamp.
- Electric components on wiring plate easily removable.
- Terminal board for cables with max section of 2,5 mm².

### Wirings (Characteristics)

Cod. ZZ	Detail
03	Insulation class CL I $\frac{1}{2}$ - Fuse 250V-T6.3A (5 x 20 mm)

### Note

- Use lamps with efficiency  $\geq$  di 90 lm/W.
- The lamps are not included in the wiring.
- On request can be realized other wiring configurations.

## PHOTOMETRICS OF REFERENCE

**Ottica mod. 0** - Lamp in view with transparent screen.

Rotosymmetric - No cut off - Type V

