

DESCRIPTION

Dimensions - Area exposed to wind pressure - Weight

Height	Width	Length	Diameter	Area exposed to wind (S)	Weight ^(A)	Weight ^(B)
895 mm	480 mm			0.275 m ²	14.5 Kg	12.5 Kg

^(A) Max weight of light fixture with electromagnetic wiring.

^(B) Max weight of light fixture with electronic wiring.

Electrical characteristics (electromagnetic wiring)

Voltage	Frequency	IP	Insulation class	Cos Φ	Oper. Temp. °C
230V	50Hz	43	CL II \square CL I \perp (on request)	> 0.9	-30... +40

Electrical characteristics (electronic wiring)

Voltage	Frequency	IP	Insulation class	Cos Φ	Oper. Temp. °C
208-277V	50/60Hz	43	CL II \square CL I \perp (on request)	> 0.9	-30... +50

Conformity

	2014/35/UE (LVD)	2014/30/UE (EMC)	2011/65/UE (RoHS)	(ErP)
--	---------------------	---------------------	----------------------	-------

Mounting system

- Suitable for suspended mounting.
- Connection with threaded tube male G 3/4" in galvanized steel.

Materials

- Cast aluminum (UNI EN 1706).
- Cast brass.
- Galvanized steel sheet.
- Acrylic (PMMA).
- Screws in stainless steel and brass.

Structure - Main components

- Upper frame with hexagonal shape in cast aluminum, for access to the auxiliary and optical compartment, equipped with a threaded tube male G3/4" for mounting to the support. The frame is hinged to the lower frame and is equipped with two small knobs for opening, six infill plates in galvanized steel sheet and six decorative finials in cast brass.
 - Lower frame with hexagonal shape in cast aluminum, composed by a basket with six linear vertical arms, and an element with six-arms and decorative terminal.
 - Wiring plate in galvanized steel sheet, easily removable.
 - Support plate for reflector in white acrylic (PMMA).
 - Lateral screens and caseback in acrylic (PMMA), transparent or frosted.
- Shock resistance: IK06.

Optics

- Reflector mod. 1 - street lighting - Installation on the side of street.
- Installation on the side of street.


Operations and maintenance

- To opening the light fixture and access to the lamp, wiring and optic compartment, loosen the two small knobs on cover and rotate the lower frame.
- During maintenance operations, no part or component is detached from the structure.
- Electric auxiliaries individually replaceable.
- During installation, follow the instructions for the correct optic orientation on the support.
- Periodic maintenance (about once a year) for external cleaning of the structure and screen from dust and smog, and the control of fastening of all screws, must be performed with light fixture switched off and cold.


Painting

- Standard color is metalized matt dark gray, type Neri.
- Other colours of RAL range on request.
- Information about paint steps used on this product in specific technical sheet.

DRAWINGS AND TECHNICAL INFORMATIONS



Front view



Plan view



Details

Code construction

To configure the complete code of luminaire, add in sequence after **Serie** code, the others parts of code: Ballast-screen (**SSS**) + Optic (**X**) + Lamp predisposition (**YY**) + Wiring type (**ZZ**). See configurations tables on the following page.

CONFIGURATION WITH ELECTROMAGNETIC WIRINGS

Screens

Cod. SSS	Light fixture series	Materials	Finiture	Shock R.
A09	700	Acrylic (PMMA)	Frosted	IK06
A11	700	Acrylic (PMMA)	Transparent	IK06

Optics

Cod. X	Type	Lighting classes	Classe IES
1	mod.1 - Fixed	Street lighting.	Cut-off

- Reflector in sheet aluminum, polished and oxidized. (thickness 1 mm, purity 99.90%).
- Lampholder regulable for a optimal positioning of lamp.
- Height of installation: from 4.5 to 6.5 meters.

Wirings (Predisposition for lamps with optical and socket)

Cod. YY	Lamps predisposition	W	Optics	Sockets
32	(MT) Metal halide - (ST) Sodium H.P.	70	1	E27
33	(MT) Metal halide - (ST) Sodium H.P.	100	1	E40
35	(MT) Metal halide - (ST) Sodium H.P.	150	1	E40

- Electromagnetic ballast with high efficiency (CELMA class EEI=A3), with thermal protection.
- Electronic ignitor (pulses until to 4.5 KV).
- Power factor correction capacitor.
- Ceramic lamp holders in relation to the type of lamp.
- Electric components on wiring plate easily removable.
- Terminal board for cables with max section of 2,5 mm².

Wirings (Characteristics)

Cod. ZZ	Details
14	Insulation class CL II ☐ - Fuse 250V-T6.3A (5 x 20 mm)

Note

- Use lamps with efficiency \geq di 90 lm/W.
- The lamps are not included in the wiring.
- On request can be realized other wiring configurations.

CONFIGURATION WITH ELECTRONIC WIRINGS

Screens

Cod. SSS	Light fixture series	Materials	Finiture	Shock R.
E09	700	Acrylic (PMMA)	Frosted	IK06
E11	700	Acrylic (PMMA)	Transparent	IK06

Optics

Cod. X	Type	Lighting classes	Classe IES
1	mod.1 - Fixed	Street lighting.	Cut-off

- Reflector in sheet aluminum, polished and oxidized. (thickness 1 mm, purity 99.90%).
- Lampholder regulable for a optimal positioning of lamp.
- Height of installation: from 4.5 to 6.5 meters.

Wirings (Predisposition for lamps with optical and socket)

Cod. YY	Lamps predisposition	W	Optics	Sockets
C4	CPO-TT (Philips)	60	1	E27
C5	CPO-TT (Philips)	90	1	E40
D4	(ST) Sodium H.P.	70	1	E27
D5	(ST) Sodium H.P.	100	1	E40

- Programmable electronic ballast with auto self diagnostics functions, protected against short circuit, over-temperature and over-voltages up to 10 KV (EN61547).
- Estimated life B10 a 80.000 h.
- Ceramic lamp holders in relation to the type of lamp.
- Electric components on wiring plate easily removable.
- Terminal board for cables with max section of 2,5 mm².

Function of electronic ballast

Cod. ZZ	Details
06	DALI - NCL (Neri Costant lumen)
13	NVL6H (automatic control integrated for lighting flux reduction) - 30% for 6 hours


Note

- Use lamps with efficiency \geq di 90 lm/W.
- The lamps are not included in the wiring.
- On request can be realized other wiring configurations.

PHOTOMETRICS OF REFERENCE

Reflector mod. 1 - Transparent screen.

Asymmetric for street lighting - Cut off - Type III



Reflector mod. 1 - Frosted screen.

Asymmetric for street lighting - Cut off - Type III

