

Compliance

CE certificated post, compliant with standard UNI EN 40-5.



Description

Modular post in UNI EN 1561 cast iron with core in S235J UNI EN 10219-1 steel, hot-galvanized to UNI EN ISO 1461 standards, corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The core (A) is made up of four tubes of different cross-sections, welded together at their junctions (B). The core must project perfectly vertically for a distance of 60 cm into a foundation plinth (P). It is provided with an M10 earthing bolt, a slot (N - height 15.0 x 4.0 cm) set 35 cm below the paving level for leading cables into the core and a 1-1/4" GAS thread (Z) at the top, used to secure the various cast iron elements by means of a nut. A heat-shrink sheath (C), minimum height 20 cm and made from composite materials (irradiated polyolefinic and butylic mastic), must be applied to the core to protect it from corrosion. The cast iron post is made up of a number of elements that are fitted over each other so as to prevent water infiltration. The elements are as follows:


- 1°) Base element height 18 cm, with an octagonal plinth (distance between flats 30 cm, height 7 cm) decorated with a scotia (D, diam. 16 cm) surmounted by a torus (E, diam. 22 cm).
- 2°) Second element height 106 cm, decorated at the base for a height of 26 cm with four leaves (F, diam. 21 cm). The upper part of the element is tapered (lower diam. 11.5 cm, top diam. 10.5 cm), and is decorated with sixteen flutes, a torus (G, diam. 13.5 cm) and four rosettes (H).
- 3°) Third element height 105 cm, composed of a lower tapered section (lower diam. 10 cm, top diam. 9 cm) decorated with a torus at each end (I - diam. 13 cm, L - diam. 11.5 cm). The top section is in the form of a capital (lower diam. 10 cm, top diam. 23 cm) decorated with four leaves (M).

The above elements are all cast as single pieces.

The total height of these first three elements is 228 cm.

Protection of surfaces

Please refer to the specification on painting procedures of the materials.



Exploded

Section

NOTE: The measurements are in centimetres.

Neri S.p.A. Property - Any reproduction and use for its own purposes is forbidden.