

Use

Suitable support for suspended light fixtures.

Materials

Made in EN-GJL HB175 cast iron and S235J UNI EN 10025 steel hot dip galvanized according to UNI EN ISO 1461.

Protection of surfaces

Please refer to the specification on painting procedures of the materials.

Dimensions and weight

Height 74 cm; width 150 cm.


Weight 47 Kg.

Description


The top section is made up of the following elements:

- 1°) An element in cast iron, height 37.5 cm, in the form of a smooth cylinder (diam. 14.5 cm) decorated with three grooves. The upper part has a junction for attaching two brackets at 180° to each other. The element is secured to the core (A) with six stainless steel M10 grub screws (B).
- 2°) A cast iron terminal, height 6 cm, in the form of a smooth cylinder (diam. 14.5 cm). This element is secured with an M8 screw (D) to the element (1°).
- 3°) Two brackets in hot-galvanized steel tube, each length 68 cm, height 65 cm, and composed of a tube with rectangular cross-section (12 x 4 cm) and a lower tube (diam. 3.3 cm) with a curve radius of 32.5 cm. The two tubes are welded together with two pegs. Each bracket is secured with two M10 screws (C) from inside element 1 and with one M8 screw (G) to the lower ring (5°).
- 4°) Two cast iron elements, each height 24 cm and in the form of a smooth cylinder (diam. 10.5 cm) decorated with a groove and a tapered bottom with a 3/4" GAS junction (F) for attaching the light fixture. These elements are fitted into the brackets (3°) and are secured with one M8 screw each (E).
- 5°) A ring in hot-galvanized steel, height 11 cm, diam. 13 cm, to which the lower end of the bracket is fixed. The ring is secured to the core (A) with two M8 grub screws.


When assembled the top section projects for 70 cm to the junction for the light fixture.



Elevation view



Section



Exploded