

### Description

Wall bracket in UNI EN 1561 cast iron, FE 360 UNI EN 10219-1 steel, hot-galvanized to UNI EN ISO 1461 standards, corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The wall bracket is composed as follows:

- 1°) A steel support tube (diam. 3.3 cm, length 70 cm) hot-galvanized. At the outer extremity the tube has a junction (D) welded to the support tube for attaching the light fixture, consisting in a ring that is tapered externally. Externally this junction has a 3/4" GAS thread for attaching the light fixture. The underside of junction is composed by an element (E) decorated with a torus, a moulding, a slot (C) for leading a 1.4 cm diameter power cable into the interior, and an earthing terminal (B).
- 2°) A cast iron bracket cast as a single piece, height 39 cm and projection 64 cm. The bracket and the support tube are joined by two collars (F) cast together with the bracket. The bracket is decorated as shown in the diagram, which also indicates the cross-section (d). Ornamentation consists in a wall plate (A – height 39 cm, width 14 cm) provided with three holes (diam. 1.3 cm) for fixing to the wall with expansion bolts, a broad volute that curves outwards and terminates in a leaf (c), and another volute (b) located at the centre between the two collars and joined at the end to the larger volute (a).

The total height of the wall bracket is 39 cm, with an effective projection of 70 cm.

### Protection of surfaces

Please refer to the specification on painting procedures of the materials.

