

Description

Wall bracket in FE 360 UNI EN 10219-1 steel, electrolytically cold-galvanized to UNI ISO 2081 standards, corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The wall bracket is composed as follows:

- 1°) A steel support tube (diam. 3.3 cm, length 60 cm). At the outer extremity the tube has a junction (C) welded to the support tube for attaching the light fixture, consisting in a ring that is tapered externally. Externally this junction has a 3/4" GAS thread for attaching the light fixture. The underside of junction is composed by an element (D) decorated with a torus, a moulding and a sphere. The support tube has a slot (B) for leading a 1.4 cm diameter power cable into the interior, and an earthing terminal (A).
- 2°) A steel bracket (section 30 x 10 mm) projecting 50 cm. The bracket, support tube and the two steel collars (E) are welded together. The ornamentation of the bracket consists in two spirals (a, b) with heights of 28 cm and 15 cm.
- 3°) A rectangular strip of steel plate, height 45 cm, width 10 cm and thickness 5 mm, with rounded corners and the bottom edge curving slightly away from the wall. The plate is welded to the support tube and the bracket and is provided with three holes (diam. 1 cm), two at the top and one at the bottom, for fixing to the wall with expansion bolts and a hole (B') for the leading cable into the tube (1°).

The total height of the wall bracket is 55 cm, with an effective projection of 60 cm.

Protection of surfaces

Please refer to the specification on painting procedures of the materials.

