

Description

Wall bracket in UNI EN 1561 cast iron and FE 360 UNI EN 10219-1 steel hot-galvanized to UNI EN ISO 1461 standards, corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The wall bracket is composed as follows:

- 1°) A steel support tube (diam. 3.3 cm, length 70 cm) hot-galvanized. At the outer extremity the tube has a junction for attaching the light fixture (D), consisting in a ring upon which the light fixture rests, a central tube with a 3/4" GAS thread complete with fixing nut in stainless steel, and a lower part (E) decorated with a torus, a moulding and a sphere. The support tube also has a slot (C) for leading a 1.4 cm diameter power cable into the interior, and an earthing terminal (B).
- 2°) A cast iron bracket with wall plate cast as a single piece, height 39 cm and projection 60 cm. The bracket and the support tube are joined by two collars (F) each decorated with two flutes and cast together with the bracket. The bracket is decorated as shown in the diagram. Ornamentation consists in a wall plate (A) height 39 cm, width 14 cm, with three holes (diam 1.3 cm) for fixing to the wall with expansion bolts, and one hole (C1) for the passage of a power cable, six branches terminating in spirals (a, b, c, d, e, f), three flat elongated leaves (g, h, i) and a double leaf terminating in three points facing downwards (l). The main branch (o) from which the leaves diverge is decorated with three flutes on each side.

The total height of the wall bracket is 39 cm, with an effective projection of 70 cm.

Protection of surfaces

Please refer to the specification on painting procedures of the materials.

