

Description

Wall bracket in UNI EN 1561 cast iron, FE 360 UNI EN 10219-1 steel hot-galvanized to UNI EN ISO 1461 standards, corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The wall bracket is composed as follows:

- 1°) A steel support tube (diam. 3.3 cm, length 100 cm) hot-galvanized. At the outer extremity the tube has a junction (D) welded to the support tube for attaching the light fixture, consisting in a ring that is tapered externally. Externally this junction has a 3/4" GAS thread for attaching the light fixture. The underside of junction is composed by an element (E) decorated with a torus, a moulding and a sphere. The support tube has a slot (C) for leading a 1.4 cm diameter power cable into the interior, and an earthing terminal (B).
- 2°) A cast iron bracket with wall plate (height 50.5 cm, projection 89 cm) cast in a single piece, decorated as shown in the diagram. The bracket and the support tube are joined by two collars (F), each decorated with two flutes and cast together with the bracket. Ornamentation consists in a wall plate (A – height 50.5 cm, width 13.5 cm) provided with three holes (diam. 1.3 cm) for fixing to the wall with expansion bolts, six branches terminating in spirals (a, b, c, d, e, f), three flat and elongated leaves (g, h, i) and a double leaf terminating in three points facing downwards. The main branch (o) from which the leaves diverge is decorated with three flutes on each side.

The total height of the wall bracket is 50.5 cm, with an effective projection of 100 cm.

Protection of surfaces

Please refer to the specification on painting procedures of the materials.

