

## **INDEX**

3	SYSTEM CONFIGURATION
4	POSTS
12	LUMINAIRE CONFIGURATION
14	MOUNTING
15	CLADDING
16	DECORATIVE LED MODULE
17	ACCESSORIES
18	PICTOR CONFIGURATION

## PICTOR SYSTEM

The Pictor system allows numerous configurations. The number of luminaires and accessories varies according to the main structure of the chosen post.

1 - Main post structure with one luminaire  
Available versions:  
h 13' 1 2/4"  
h 16' 4 3/4"  
h 19' 8 1/4"

2 - Main post structure with two luminaires  
Available versions:  
h 13' 1 2/4"  
h 16' 4 3/4"  
h 19' 8 1/4"

3 - Main post structure with two staggered luminaires  
Available versions:  
h 16' 4 3/4"  
h 19' 8 1/4"

4 - Hand hole


5 - Cladding accessory available in three different finishes.

6 - Decorative LED module accessory

7 - Post base cover accessory

Other accessories available on request:

- Terminal block
- PIR presence detector
- NEMA Socket (3 or 7 pin)



## MAIN STRUCTURE POST H 13' 1 2/4"

### Dimensions - Area - Weight

Height	Width	Lenght	Weight	EPA
13' 1 2/4"	3 7/8"	7 7/8"	80.46 lb	6.2 ft <sup>2</sup>

### Materials

- Lamp post in extruded aluminum.
- Steel fastening devices.

### Structure - Main components

- Aluminum profile 7 7/8" x 3 7/8" (A), height 13' 1 2/4".
- Arm (B) in aluminum profile 7 7/8" x 3 7/8" (length 35 3/8") with integrated lighting system.

### Standard equipment

- Slot (15 6/8" x 4 6/8") for installation of terminal board, with or without fuse.
- Hand hole (C) (15 6/8" x 4 5/8") to close the slot for terminal board with the Neri logo on it.
- Hole (6 6/8" x 2 3/8") at the centre of flange for passage of electric cables.

### Embedded root mounting

- With embedded root to be cemented to the foundation plinth (embedded root depth 31 4/8").

### Flange mounting

- Square flange 10 4/8" x 10 4/8" (thickness 1") with blunted edges, for mounting with four anchors bolts to the foundation plinth (anchors and bolts are not supplied).
- Set-up for mounting with flange and hidden flange (3 7/8" below the final pavement level).

### Painting

- Standard colors: Neri grey, pure white (RAL9010), jet black (RAL9005), moss green (RAL6005), white aluminum (RAL9006), grey aluminum (RAL9007).

### Accessories (on request)

- Post base cover accessory.
- LED decorative module.
- Decorative cladding - Wood, bronze and white aluminum finishes.
- Terminal block.

## LUMINAIRE

### Compliance

- In compliance with UL Standard 1598, UL8750.



### Construction

- External frame in extruded aluminum.
- Shield in prismatic tempered glass.
- Integrated heat sink in aluminum.
- White internal reflector.
- Dedicated space for any surge protection devices or remote control systems.
- Suitable for wet location.

### Materials

- Extruded aluminum.
- Prismatic flat glass.
- Aluminum sheet.
- Stainless steel screws.

### Electrical data

- Voltage: 120-277V (universal).
- Rated power: from 19.6 W to 93.7 W.
- Frequency: 50/60Hz.
- Protection rating: IP66, IK09 (Prismatic glass).
- Operating temp.: -31°F / +122°F.
- Electronic power supply with protection against short circuits, overheating and power surges with an estimated duration of 100,000 h.
- Supplied with power cable.
- Standard surge protection 10kV/10kV.


### Operation and maintenance

- Periodic maintenance for the external cleaning of the structure and the screens from dust and smog and tightening control to the support.

### Accessories (on request)

- PIR presence detector.
- NEMA Socket (3 or 7 pin).

## DRAWINGS



MAIN STRUCTURE POST H 13' 1 2/4"

Dimensions - Area - Weight

Height	Width	Lenght	Weight	EPA
13' 1 2/4"	3 7/8"	7 7/8"	105.82 lb	7.2 ft²

Materials

- Lamp post in extruded aluminum.
- Steel fastening devices.

Structure - Main components

- Aluminum profile 7 7/8" x 3 7/8" (A), height 13' 1 2/4".
- Double arm (B) in aluminum profile 7 7/8" x 3 7/8" (35 3/8") with integrated lighting system.

Standard equipment

- Slot (15 6/8" x 4 6/8") for installation of terminal board, with or without fuse.
- Hand hole (C) (15 6/8" x 4 5/8") to close the slot for terminal board with the Neri logo on it.
- Hole (6 6/8" x 2 3/8") at the centre of flange for passage of electric cables.

Embedded root mounting

- With embedded root to be cemented to the foundation plinth (embedded root depth 31 4/8").

Flange mounting

- Square flange 10 4/8" x 10 4/8" (thickness 1") with blunted edges, for mounting with four anchors bolts to the foundation plinth (anchors and bolts are not supplied).
- Set-up for mounting with flange and hidden flange (3 7/8" below the final pavement level).

Painting

- Standard colors: Neri grey, pure white (RAL9010), jet black (RAL9005), moss green (RAL6005), white aluminum (RAL9006), grey aluminum (RAL9007).

Accessories (on request)

- Post base cover accessory.
- LED decorative module.
- Decorative cladding - Wood, bronze and white aluminum finishes.
- Terminal block.

LUMINAIRE

Compliance

- In compliance with UL Standard 1598, UL8750.



Construction

- External frame in extruded aluminum.
- Shield in prismatic tempered glass.
- Integrated heat sink in aluminum.
- White internal reflector.
- Dedicated space for any surge protection devices or remote control systems.
- Suitable for wet location.

Materials

- Extruded aluminum.
- Prismatic flat glass.
- Aluminum sheet.
- Stainless steel screws.

Electrical data

- Voltage: 120-277V (universal).
- Rated power: from 19.6 W to 93.7 W.
- Frequency: 50/60Hz.
- Protection rating: IP66, IK09 (Prismatic glass).
- Operating temp.: -31°F / +122°F.
- Electronic power supply with protection against short circuits, overheating and power surges with an estimated duration of 100,000 h.
- Supplied with power cable.
- Standard surge protection 10kV/10kV.


Operation and maintenance

- Periodic maintenance for the external cleaning of the structure and the screens from dust and smog and tightening control to the support.

Accessories (on request)

- PIR presence detector.
- NEMA Socket (3 or 7 pin).

DRAWINGS



MAIN STRUCTURE POST H 16' 4 3/4"

Dimensions - Area - Weight

Height	Width	Lenght	Weight	EPA
16' 4 3/4"	3 7/8"	7 7/8"	91.49 lb	7.4 ft <sup>2</sup>

Materials

- Lamp post in extruded aluminum.
- Steel fastening devices.

Structure - Main components

- Aluminum profile 7 7/8" x 3 7/8" (A), height 16' 4 3/4".
- Arm (B) in aluminum profile 7 7/8" x 3 7/8" (lenght 35 3/8") with integrated lighting system.

Standard equipment

- Slot (15 6/8" x 4 6/8") for installation of terminal board, with or without fuse.
- Hand hole (C) (15 6/8" x 4 5/8") to close the slot for terminal board with the Neri logo on it.
- Hole (6 6/8" x 2 3/8") at the centre of flange for passage of electric cables.

Embedded root mounting

- With embedded root to be cemented to the foundation plinth (embedded root depth 31 4/8").

Flange mounting

- Square flange 10 4/8" x 10 4/8" (thickness 1") with blunted edges, for mounting with four anchors bolts to the foundation plinth (anchors and bolts are not supplied).
- Set-up for mounting with flange and hidden flange (3 7/8" below the final pavement level).

Painting

- Standard colors: Neri grey, pure white (RAL9010), jet black (RAL9005), moss green (RAL6005), white aluminum (RAL9006), grey aluminum (RAL9007).

Accessories (on request)

- Post base cover accessory.
- LED decorative module.
- Decorative cladding - Wood, bronze and white aluminum finishes.
- Terminal block.

LUMINAIRE

Compliance

- In compliance with UL Standard 1598, UL8750.



Construction

- External frame in extruded aluminum.
- Shield in prismatic tempered glass.
- Integrated heat sink in aluminum.
- White internal reflector.
- Dedicated space for any surge protection devices or remote control systems.
- Suitable for wet location.

Materials

- Extruded aluminum.
- Prismatic flat glass.
- Aluminum sheet.
- Stainless steel screws.

Electrical data

- Voltage: 120-277V (universal).
- Rated power: from 19.6 W to 93.7 W.
- Frequency: 50/60Hz.
- Protection rating: IP66, IK09 (Prismatic glass).
- Operating temp.: -31°F / +122°F.
- Electronic power supply with protection against short circuits, overheating and power surges with an estimated duration of 100,000 h.
- Supplied with power cable.
- Standard surge protection 10kV/10kV.


Operation and maintenance

- Periodic maintenance for the external cleaning of the structure and the screens from dust and smog and tightening control to the support.

Accessories (on request)

- PIR presence detector.
- NEMA Socket (3 or 7 pin).

DRAWINGS



MAIN STRUCTURE POST H 16' 4 3/4"

Dimensions - Area - Weight

Height	Width	Lenght	Weight	EPA
16' 4 3/4"	3 7/8"	7 7/8"	116.84 lb	8.5 ft <sup>2</sup>

Materials

- Lamp post in extruded aluminum.
- Steel fastening devices.

Structure - Main components

- Aluminum profile 7 7/8" x 3 7/8" (A), height 16' 4 3/4".
- Double arm (B) in aluminum profile 7 7/8" x 3 7/8" (35 3/8") with integrated lighting system.

Standard equipment

- Slot (15 6/8" x 4 6/8") for installation of terminal board, with or without fuse.
- Hand hole (C) (15 6/8" x 4 5/8") to close the slot for terminal board with the Neri logo on it.
- Hole (6 6/8" x 2 3/8") at the centre of flange for passage of electric cables.

Embedded root mounting

- With embedded root to be cemented to the foundation plinth (embedded root depth 31 4/8").

Flange mounting

- Square flange 10 4/8" x 10 4/8" (thickness 1") with blunted edges, for mounting with four anchors bolts to the foundation plinth (anchors and bolts are not supplied).
- Set-up for mounting with flange and hidden flange (3 7/8" below the final pavement level).

Painting

- Standard colors: Neri grey, pure white (RAL9010), jet black (RAL9005), moss green (RAL6005), white aluminum (RAL9006), grey aluminum (RAL9007).

Accessories (on request)

- Post base cover accessory.
- LED decorative module.
- Decorative cladding - Wood, bronze and white aluminum finishes.
- Terminal block.

LUMINAIRE

Compliance

- In compliance with UL Standard 1598, UL8750.



Construction

- External frame in extruded aluminum.
- Shield in prismatic tempered glass.
- Integrated heat sink in aluminum.
- White internal reflector.
- Dedicated space for any surge protection devices or remote control systems.
- Suitable for wet location.

Materials

- Extruded aluminum.
- Prismatic flat glass.
- Aluminum sheet.
- Stainless steel screws.

Electrical data

- Voltage: 120-277V (universal).
- Rated power: from 19.6 W to 93.7 W.
- Frequency: 50/60Hz.
- Protection rating: IP66, IK09 (Prismatic glass).
- Operating temp.: -31°F / +122°F.
- Electronic power supply with protection against short circuits, overheating and power surges with an estimated duration of 100,000 h.
- Supplied with power cable.
- Standard surge protection 10kV/10kV.


Operation and maintenance

- Periodic maintenance for the external cleaning of the structure and the screens from dust and smog and tightening control to the support.

Accessories (on request)

- PIR presence detector.
- NEMA Socket (3 or 7 pin).

DRAWINGS



MAIN STRUCTURE POST H 16' 4 3/4"

Dimensions - Area - Weight

Height	Width	Lenght	Weight	EPA
16' 4 3/4"	3 7/8"	7 7/8"	119.05 lb	8.5 ft²

- Materials
- Lamp post in extruded aluminum.
  - Steel fastening devices.

- Structure - Main components
- Aluminum profile 7 7/8" x 3 7/8" (A), height 16' 4 3/4".
  - Double staggered arm (B) in aluminum profile 7 7/8" x 3 7/8" (35 3/8") with integrated lighting system.

- Standard equipment
- Slot (15 6/8" x 4 6/8") for installation of terminal board, with or without fuse.
  - Hand hole (C) (15 6/8" x 4 5/8") to close the slot for terminal board with the Neri logo on it.
  - Hole (6 6/8" x 2 3/8") at the centre of flange for passage of electric cables.

- Embedded root mounting
- With embedded root to be cemented to the foundation plinth (embedded root depth 31 4/8").

- Flange mounting
- Square flange 10 4/8" x 10 4/8" (thickness 1") with blunted edges, for mounting with four anchors bolts to the foundation plinth (anchors and bolts are not supplied).
  - Set-up for mounting with flange and hidden flange (3 7/8" below the final pavement level).

- Painting
- Standard colors: Neri grey, pure white (RAL9010), jet black (RAL9005), moss green (RAL6005), white aluminum (RAL9006), grey aluminum (RAL9007).

- Accessories (on request)
- Post base cover accessory.
  - LED decorative module.
  - Decorative cladding - Wood, bronze and white aluminum finishes.
  - Terminal block.

LUMINAIRE

- Compliance
- In compliance with UL Standard 1598, UL8750.



- Construction
- External frame in extruded aluminum.
  - Shield in prismatic tempered glass.
  - Integrated heat sink in aluminum.
  - White internal reflector.
  - Dedicated space for any surge protection devices or remote control systems.
  - Suitable for wet location.


- Materials
- Extruded aluminum.
  - Prismatic flat glass.
  - Aluminum sheet.
  - Stainless steel screws.

- Electrical data
- Voltage: 120-277V (universal).
  - Rated power: from 19.6 W to 93.7 W.
  - Frequency: 50/60Hz.
  - Protection rating: IP66, IK09 (Prismatic glass).
  - Operating temp.: -31°F / +122°F.
  - Electronic power supply with protection against short circuits, overheating and power surges with an estimated duration of 100,000 h.
  - Supplied with power cable.
  - Standard surge protection 10kV/10kV.

- Operation and maintenance
- Periodic maintenance for the external cleaning of the structure and the screens from dust and smog and tightening control to the support.

- Accessories (on request)
- PIR presence detector.
  - NEMA Socket (3 or 7 pin).

DRAWINGS





## MAIN STRUCTURE POST H 19' 8 1/4"

## DRAWINGS

## Dimensions - Area - Weight

Height	Width	Lenght	Weight	EPA
19' 8 1/4"	3 7/8"	7 7/8"	102.51 lb	8.7 ft <sup>2</sup>

## Materials

- Lamp post in extruded aluminum.
- Steel fastening devices.

## Structure - Main components

- Aluminum profile 7 7/8" x 3 7/8" (A), height 19' 8 1/4".
- Arm (B) in aluminum profile 7 7/8" x 3 7/8" (length 35 3/8") with integrated lighting system.

## Standard equipment

- Slot (15 6/8" x 4 6/8") for installation of terminal board, with or without fuse.
- Hand hole (C) (15 6/8" x 4 5/8") to close the slot for terminal board with the Neri logo on it.
- Hole (6 6/8" x 2 3/8") at the centre of flange for passage of electric cables.

## Embedded root mounting

- With embedded root to be cemented to the foundation plinth (embedded root depth 31 4/8").

## Flange mounting

- Square flange 10 4/8" x 10 4/8" (thickness 1") with blunted edges, for mounting with four anchors bolts to the foundation plinth (anchors and bolts are not supplied).
- Set-up for mounting with flange and hidden flange (3 7/8" below the final pavement level).

## Painting

- Standard colors: Neri grey, pure white (RAL9010), jet black (RAL9005), moss green (RAL6005), white aluminum (RAL9006), grey aluminum (RAL9007).

## Accessories (on request)

- Post base cover accessory.
- LED decorative module.
- Decorative cladding - Wood, bronze and white aluminum finishes.
- Terminal block.

## LUMINAIRE

## Compliance

- In compliance with UL Standard 1598, UL8750.



## Construction

- External frame in extruded aluminum.
- Shield in prismatic tempered glass.
- Integrated heat sink in aluminum.
- White internal reflector.
- Dedicated space for any surge protection devices or remote control systems.
- Suitable for wet location.

## Materials

- Extruded aluminum.
- Prismatic flat glass.
- Aluminum sheet.
- Stainless steel screws.

## Electrical data


- Voltage: 120-277V (universal).
- Rated power: from 19.6 W to 93.7 W.
- Frequency: 50/60Hz.
- Protection rating: IP66, IK09 (Prismatic glass).
- Operating temp.: -31°F / +122°F.
- Electronic power supply with protection against short circuits, overheating and power surges with an estimated duration of 100,000 h.
- Supplied with power cable.
- Standard surge protection 10kV/10kV.

## Operation and maintenance

- Periodic maintenance for the external cleaning of the structure and the screens from dust and smog and tightening control to the support.

## Accessories (on request)

- PIR presence detector.
- NEMA Socket (3 or 7 pin).



**MAIN STRUCTURE POST H 19' 8 1/4"****Dimensions - Area - Weight**

Height	Width	Lenght	Weight	EPA
19' 8 1/4"	3 7/8"	7 7/8"	127.86 lb	9.8 ft <sup>2</sup>

**Materials**

- Lamp post in extruded aluminum.
- Steel fastening devices.

**Structure - Main components**

- Aluminum profile 7 7/8" x 3 7/8" (A), height 19' 8 1/4".
- Double arm (B) in aluminum profile 7 7/8" x 3 7/8" (length 35 3/8") with integrated lighting system.

**Standard equipment**

- Slot (15 6/8" x 4 6/8") for installation of terminal board, with or without fuse.
- Hand hole (C) (15 6/8" x 4 5/8") to close the slot for terminal board with the Neri logo on it.
- Hole (6 6/8" x 2 3/8") at the centre of flange for passage of electric cables.

**Embedded root mounting**

- With embedded root to be cemented to the foundation plinth (embedded root depth 31 4/8").

**Flange mounting**

- Square flange 10 4/8" x 10 4/8" (thickness 1") with blunted edges, for mounting with four anchors bolts to the foundation plinth (anchors and bolts are not supplied).
- Set-up for mounting with flange and hidden flange (3 7/8" below the final pavement level).

**Painting**

- Standard colors: Neri grey, pure white (RAL9010), jet black (RAL9005), moss green (RAL6005), white aluminum (RAL9006), grey aluminum (RAL9007).

**Accessories (on request)**

- Post base cover accessory.
- LED decorative module.
- Decorative cladding - Wood, bronze and white aluminum finishes.
- Terminal block.

**LUMINAIRE****Compliance**

- In compliance with UL Standard 1598, UL8750.

**Construction**

- External frame in extruded aluminum.
- Shield in prismatic tempered glass.
- Integrated heat sink in aluminum.
- White internal reflector.
- Dedicated space for any surge protection devices or remote control systems.
- Suitable for wet location.

**Materials**

- Extruded aluminum.
- Prismatic flat glass.
- Aluminum sheet.
- Stainless steel screws.

**Electrical data**


- Voltage: 120-277V (universal).
- Rated power: from 19.6 W to 93.7 W.
- Frequency: 50/60Hz.
- Protection rating: IP66, IK09 (Prismatic glass).
- Operating temp.: -31°F / +122°F.
- Electronic power supply with protection against short circuits, overheating and power surges with an estimated duration of 100,000 h.
- Supplied with power cable.
- Standard surge protection 10kV/10kV.

**Operation and maintenance**

- Periodic maintenance for the external cleaning of the structure and the screens from dust and smog and tightening control to the support.

**Accessories (on request)**

- PIR presence detector.
- NEMA Socket (3 or 7 pin).

**DRAWINGS**

## MAIN STRUCTURE POST H 19' 8 1/4"

## Dimensions - Area - Weight

Height	Width	Lenght	Weight	EPA
19' 8 1/4"	3 7/8"	7 7/8"	130.07 lb	9.8 ft <sup>2</sup>

## Materials

- Lamp post in extruded aluminum.
- Steel fastening devices.

## Structure - Main components

- Aluminum profile 7 7/8" x 3 7/8" (A), height 19' 8 1/4".
- Double staggered arm (B) in aluminum profile 7 7/8" x 3 7/8" (length 35 3/8") with integrated lighting system.

## Standard equipment

- Slot (15 6/8" x 4 6/8") for installation of terminal board, with or without fuse.
- Hand hole (C) (15 6/8" x 4 5/8") to close the slot for terminal board with the Neri logo on it.
- Hole (6 6/8" x 2 3/8") at the centre of flange for passage of electric cables.

## Embedded root mounting

- With embedded root to be cemented to the foundation plinth (embedded root depth 31 4/8").

## Flange mounting

- Square flange 10 4/8" x 10 4/8" (thickness 1") with blunted edges, for mounting with four anchors bolts to the foundation plinth (anchors and bolts are not supplied).
- Set-up for mounting with flange and hidden flange (3 7/8" below the final pavement level).

## Painting

- Standard colors: Neri grey, pure white (RAL9010), jet black (RAL9005), moss green (RAL6005), white aluminum (RAL9006), grey aluminum (RAL9007).

## Accessories (on request)

- Post base cover accessory.
- LED decorative module.
- Decorative cladding - Wood, bronze and white aluminum finishes.
- Terminal block.

## LUMINAIRE

## Compliance

- In compliance with UL Standard 1598, UL8750.



## Construction

- External frame in extruded aluminum.
- Shield in prismatic tempered glass.
- Integrated heat sink in aluminum.
- White internal reflector.
- Dedicated space for any surge protection devices or remote control systems.
- Suitable for wet location.

## Materials

- Extruded aluminum.
- Prismatic flat glass.
- Aluminum sheet.
- Stainless steel screws.

## Electrical data

- Voltage: 120-277V (universal).
- Rated power: from 19.6 W to 93.7 W.
- Frequency: 50/60Hz.
- Protection rating: IP66, IK09 (Prismatic glass).
- Operating temp.: -31°F / +122°F.
- Electronic power supply with protection against short circuits, overheating and power surges with an estimated duration of 100,000 h.
- Supplied with power cable.
- Standard surge protection 10kV/10kV.


## Operation and maintenance

- Periodic maintenance for the external cleaning of the structure and the screens from dust and smog and tightening control to the support.

## Accessories (on request)

- PIR presence detector.
- NEMA Socket (3 or 7 pin).

## DRAWINGS



# NERI

## STANDARD | PRISMATIC GLASS


Standard version is equipped with seven lighting distribution and eight lumen output choices. Light distributions available are symmetric and asymmetric [Types: II, III (3x), IV (2x), V]; lumen outputs range from 2,500lm to 12,000lm.

### Optical features

- LED Type: Lumileds Luxeon 5050
- Source efficiency LED: 164 lm/W @ Tj=25°C, 800 mA, 3000K
- Source efficiency LED: 169 lm/W @ Tj=25°C, 800 mA, 4000K
- Lumen output: from 2,500 to 12,000 lm.
- Color temperature: 3,000K or 4,000K (2,200K and 2,700K on request).
- Chromatic Rendering Index: > 80
- Estimated life: 100,000 hours (L90 - Tq25°C).

### Type II - D

Distribution type: Asymmetric



LOR 100%  
Full Cutoff



## DRIVER FUNCTION:

### Description

#### 0-10V + NCL

(Analogic control + Neri Constant Lumen)

#### ON/OFF + NCL

(On / Off + Neri Constant Lumen)

## 3,000K

lm tot	W tot	lm/W
2,500	20.5	122
3,500	27.0	129
4,500	34.6	130
6,000	48.4	124
7,500	58.8	127
9,000	71.9	125
10,500	81.1	130
12,000	93.7	128

## Lamp Post type:

Rev.03


01/2024

## 4,000K

lm tot	W tot	lm/W
2,500	19.6	128
3,500	25.8	136
4,500	32.8	137
6,000	45.9	131
7,500	55.8	134
9,000	67.9	133
10,500	76.8	137
12,000	88.6	135

### Type III - B

Distribution type: Asymmetric




LOR 100%  
Full Cutoff



### Type III - C

Distribution type: Asymmetric




LOR 100%  
Full Cutoff




### Type III - H

Distribution type: Asymmetric




LOR 100%  
Full Cutoff




LCS Zone	Angles	% Lamp	% Lum
FL	0° - 30°	15.8	15.8
FM	30° - 60°	40.7	40.7
FH	60° - 80°	13.5	13.5
FVH	80° - 90°	0.7	0.7
BL	0° - 30°	9.0	9.0
BM	30° - 60°	15.3	15.3
BH	60° - 80°	4.8	4.8
BVH	80° - 90°	0.2	0.2
UL	90° - 100°	0.0	0.0
UH	100° - 180°	0.0	0.0
Totals		100.0	100.0

2,500lm - BUG: B1 U0 G1




LCS Zone	Angles	% Lamp	% Lum
FL	0° - 30°	16.6	16.6
FM	30° - 60°	40.3	40.3
FH	60° - 80°	13.0	13.0
FVH	80° - 90°	0.7	0.7
BL	0° - 30°	9.3	9.3
BM	30° - 60°	14.9	14.9
BH	60° - 80°	5.0	5.0
BVH	80° - 90°	0.2	0.2
UL	90° - 100°	0.0	0.0
UH	100° - 180°	0.0	0.0
Totals		100.0	100.0

2,500lm - BUG: B1 U0 G1



LCS Zone	Angles	% Lamp	% Lum
FL	0° - 30°	14.6	14.6
FM	30° - 60°	38.4	38.4
FH	60° - 80°	14.6	14.6
FVH	80° - 90°	0.8	0.8
BL	0° - 30°	8.3	8.3
BM	30° - 60°	16.7	16.7
BH	60° - 80°	6.4	6.4
BVH	80° - 90°	0.3	0.3
UL	90° - 100°	0.0	0.0
UH	100° - 180°	0.0	0.0
Totals		100.0	100.0

2,500lm - BUG: B1 U0 G1






LCS Zone	Angles	% Lamp	% Lum
FL	0° - 30°	13.5	13.5
FM	30° - 60°	39.8	39.8
FH	60° - 80°	15.9	15.9
FVH	80° - 90°	0.9	0.9
BL	0° - 30°	8.6	8.6
BM	30° - 60°	15.9	15.9
BH	60° - 80°	5.3	5.3
BVH	80° - 90°	0.2	0.2
UL	90° - 100°	0.0	0.0
UH	100° - 180°	0.0	0.0
Totals		100.0	100.0

2,500lm - BUG: B1 U0 G1

**STANDARD | PRISMATIC GLASS**  
Standard version is equipped with seven lighting distribution and eight lumen output choices. Light distributions available are symmetric and asymmetric [Types: II, III (3x), IV (2x), V]; lumen outputs range from 2,500lm to 12,000lm.

- Optical features
- LED Type: Lumileds Luxeon 5050
  - Source efficiency LED: 164 lm/W @ Tj=25°C, 800 mA, 3000K
  - Source efficiency LED: 169 lm/W @ Tj=25°C, 800 mA, 4000K
  - Lumen output: from 2,500 to 12,000 lm.
  - Color temperature: 3,000K or 4,000K (2,200K and 2,700K on request).
  - Chromatic Rendering Index: > 80
  - Estimated life: 100,000 hours (L90 - Tq25°C).

**Type IV - A**  
Distribution type: Forward throw



LCS Zone	Angles	% Lamp	% Lum
FL	0° - 30°	11.0	11.0
FM	30° - 60°	38.8	38.8
FH	60° - 80°	18.5	18.5
FVH	80° - 90°	1.1	1.1
BL	0° - 30°	8.1	8.1
BM	30° - 60°	16.5	16.5
BH	60° - 80°	5.8	5.8
BVH	80° - 90°	0.3	0.3
UL	90° - 100°	0.0	0.0
UH	100° - 180°	0.0	0.0
Totals		100.0	100.0

2,500lm - BUG: B1 U0 G1

Project location:	
Project name:	
Model code #:	Date




**DRIVER FUNCTION:**  
**Description**  
**0-10V + NCL**  
(Analogic control + Neri Constant Lumen)  
**ON/OFF + NCL**  
(On / Off + Neri Constant Lumen)

3,000K		
lm tot	W tot	lm/W
2,500	20.5	122
3,500	27.0	129
4,500	34.6	130
6,000	48.4	124
7,500	58.8	127
9,000	71.9	125
10,500	81.1	130
12,000	93.7	128

Lamp Post type:	
Rev.03	01/2024

4,000K		
lm tot	W tot	lm/W
2,500	19.6	128
3,500	25.8	136
4,500	32.8	137
6,000	45.9	131
7,500	55.8	134
9,000	67.9	133
10,500	76.8	137
12,000	88.6	135



**Type IV - C**  
Distribution type: Forward throw



LCS Zone	Angles	% Lamp	% Lum
FL	0° - 30°	13.9	13.9
FM	30° - 60°	39.6	39.6
FH	60° - 80°	15.7	15.7
FVH	80° - 90°	0.9	0.9
BL	0° - 30°	8.7	8.7
BM	30° - 60°	15.7	15.7
BH	60° - 80°	5.4	5.4
BVH	80° - 90°	0.2	0.2
UL	90° - 100°	0.0	0.0
UH	100° - 180°	0.0	0.0
Totals		100.0	100.0

2,500lm - BUG: B1 U0 G1

**Type V - A**  
Distribution type: Rotosymmetric



LCS Zone	Angles	% Lamp	% Lum
FL	0° - 30°	8.2	8.2
FM	30° - 60°	29.2	29.2
FH	60° - 80°	12.0	12.0
FVH	80° - 90°	0.6	0.6
BL	0° - 30°	8.2	8.2
BM	30° - 60°	29.2	29.2
BH	60° - 80°	12.0	12.0
BVH	80° - 90°	0.6	0.6
UL	90° - 100°	0.0	0.0
UH	100° - 180°	0.0	0.0
Totals		100.0	100.0

2,500lm - BUG: B1 U0 G1

Project location:	
Project name:	
Model code #:	Date

Lamp Post type:	
Rev.03	01/2024


## MOUNTING

The Pictor system allows several types of installation on the ground.

The system is set-up for mounting with flange and hidden flange (3 7/8" below the final pavement level) and also with embedded root to be cemented to the foundation plinth.

A post base cover accessory is available on request.


Mounting with hide flange



Ground fixing element - Flange (A)

Cod. 9525.389.010


Mounting with flange



Post (B)

Cod. 9515.147.001 - 13' 1 2/4", single arm  
Cod. 9515.147.003 - 13' 1 2/4", double arm  
Cod. 9515.147 - 16' 4 3/4", single arm  
Cod. 9515.147.004 - 16' 4 3/4", double arm  
Cod. 9515.147.007 - 16' 4 3/4", staggered arm  
Cod. 9515.147.002 - 19' 8 1/4", single arm  
Cod. 9515.147.005 - 19' 8 1/4", double arm  
Cod. 9515.147.006 - 19' 8 1/4", staggered arm


Mounting with base post cover




Post base cover (C)

Cod. OPPIC0000S000001

Flange detail



Embedded root - Concrete



Embedded root element (A)

Cod. 9525.389.008

CLADDING

The Pictor system allows the installation of a decorative cladding\* available in three different finishes.

Dimensions for post H 13' 1 2/4":  
12' 3 1/4" x 6 2/8"

Dimensions for post H 16' 4 3/4":  
15' 6 2/4" x 6 2/8"

Dimensions for post H 19' 8 1/4":  
18' 10" x 6 2/8"

\*The cladding can be configured in the version with a single lighting fixture only and will be positioned on the front frame (Fig. 1).

Wood finish



Cod. 9515.137.011A - H post 13' 1 2/4"  
Cod. 9515.137.012A - H post 16' 4 3/4"  
Cod. 9515.137.013A - H post 19' 8 1/4"

Bronze finish

Cod. 9515.137.017A - H post 13' 1 2/4"  
Cod. 9515.137.018A - H post 16' 4 3/4"  
Cod. 9515.137.019A - H post 19' 8 1/4"

White aluminium finish

Cod. 9515.137.014A - H post 13' 1 2/4"  
Cod. 9515.137.015A - H post 16' 4 3/4"  
Cod. 9515.137.016A - H post 19' 8 1/4"




FINISH

Standard color for the system is Neri grey.

Finishes available for decorative cladding:

- Wood
- Bronze
- White aluminium




Neri grey



Wood



Bronze



White aluminium  
RAL 9006

## DECORATIVE LED MODULE

The Pictor system allows the installation of a decorative LED module\* in all available versions; the module is equipped with a customizable protection screen.

The available dimensions are 3' 3 1/4" x 3 1/8" and 12 5/8" x 3 1/8".

Available CCT:  
3,000K - 4,000K- RGB

Driver functions  
ON-OFF, DMX

\*Only one decorative LED module can be installed in each chosen configuration. The module can be positioned at a minimum height of 5' 3" on the front frame (Fig. 1) or on the rear frame (post hatch) (Fig. 2).

### Decorative LED module (h 12 5/8")

Cod. OPPIC0000S000002 - 3,000K  
Cod. OPPIC0000S000003 - 4,000K  
Cod. OPPIC0000S000004 - RGB

### Decorative LED module (h 3' 3 1/4")

Cod. OPPIC0000S000005 - 3,000K  
Cod. OPPIC0000S000006 - 4,000K  
Cod. OPPIC0000S000007 - RGB





Fig. 1

Fig. 2



## POST BASE COVER ACCESSORY

### Dimensions - Weight

Height	Width	Length	Weight
3 5/8"	11 2/8"	11 2/8"	5.51 lb

Post base cover for posts with rectangular section 3 7/8" x 7 7/8".

### Materials

- Galvanized steel sheet.
- Stainless steel screws.
- Plastic closing cap.

### Structure - Main components

- The base cover is made up by two piece "clam-shell" cover in steel sheet, 1/8" thick.

### Fixing

- The base cover is designed for post attachment in two places with n.2 M8 screws.

### Protection of the surfaces

- See the specific descriptions on the painting cycles of the materials.



### Operations and maintenance

- Refer to the product installation and maintenance manual.
- It is the responsibility of the installer to install correctly in accordance with applicable regulations.

### Painting


- Standard colors: Neri grey, pure white (RAL9010), jet black (RAL9005), moss green (RAL6005), white aluminum (RAL9006), grey aluminum (RAL9007).

## DRAWINGS



## PICTOR

The Pictor system allows numerous configurations. The number of luminaires and accessories varies according to the main structure of the chosen post.



Project location:	
Project name:	
Model code #:	Date

Lamp Post type:	
Rev.03	01/2024

### PICTOR CONFIGURATION # \_\_\_\_\_

Luminaire configuration number to be also written in the lamp post configuration page.

#### ☐ PICTOR - POST

##### Post height

- ☐ 13' 1 2/4"      ☐ 19' 8 1/4"  
☐ 16' 4 3/4"

#### ☐ PICTOR - LUMINAIRES

##### Luminaires number

- ☐ 1 - Post top mounting  
☐ 2 - Post top mounting with double arm  
☐ 2 - Post top mounting with double staggered arm\*

\* Available with 16' 4 3/4" and 19' 8 1/4" post

#### ☐ PICTOR - MOUNTING

##### Post mounting

- ☐ Flange mounting      ☐ Embedded root mounting

#### ☐ PICTOR - LUMINAIRE CONFIGURATION

Optic system	CCT	Lumen output	Driver function	Aperture lens
<input type="checkbox"/> Type II	<input type="checkbox"/> 3,000K	<input type="checkbox"/> 2,500	<input type="checkbox"/> 0-10V + NCL	<input type="checkbox"/> Prismatic flat glass
<input type="checkbox"/> Type III (B, C or H)	<input type="checkbox"/> 4,000K	<input type="checkbox"/> 3,500	<input type="checkbox"/> ON/OFF + NCL	
<input type="checkbox"/> Type IV (A or C)	<input type="checkbox"/> 2,200K*	<input type="checkbox"/> 4,500		
<input type="checkbox"/> Type V	<input type="checkbox"/> 2,700K*	<input type="checkbox"/> 6,000		
		<input type="checkbox"/> 7,500		
		<input type="checkbox"/> 9,000		
		<input type="checkbox"/> 10,500		
		<input type="checkbox"/> 12,000		

\* On request

#### ☐ PICTOR - CLADDING

##### Decorative cladding finish\*

- ☐ Wood      ☐ White aluminum  
☐ Bronze

\*The cladding can be configured in the version with a single lighting fixture only and will be positioned on the front frame.

#### ☐ PICTOR - DECORATIVE LED MODULE

##### Dimensions and CCT\*

- ☐ 12 5/8" x 3 1/8"      ☐ 3,000K  
☐ 3' 3 1/4" x 3 1/8"      ☐ 4,000K  
☐ RGB

\*Only one decorative LED module can be installed in each chosen configuration. The module can be positioned at a minimum height of 5' 3" on the front frame or on the rear frame (hand hole).

#### ☐ PICTOR - ACCESSORIES

##### Available accessories on request

- ☐ Post base cover      ☐ PIR Presence detector  
☐ Terminal block      ☐ NEMA Socket (3 or 7 pin).

#### ☐ PICTOR - COLOR

##### Paint choice

- ☐ Neri grey      ☐ Pure White (RAL9010)  
☐ Jet Black (RAL9005)      ☐ Moss Green (RAL6005)  
☐ Grey Aluminum (RAL9007)      ☐ White Aluminum (RAL9006)