

Project location:			
Project name:			
Model #:	4220.075.001	Date	

Description

Wall bracket made from elements FE 360 UNI EN 10219-1 steel hot-galvanized to UNI ISO 1461 standards, corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The wall bracket is composed as follows:

1°) a brackets made of hot-galvanised steel, each 30 1/4" long, 5' 9" high, comprising a horizontal tube (2 1/4" diam.); a tube (G ) 7" long (3" diam.) with inner threading 3/4" GAS (G) for fastening the light fixture, with upper plastic inspection plug (F); a lower curved tube (1 3/4" diam.) (H) fastened to the horizontal tube by means of two spaced plates. Ends closed with plastic plugs (E). The support tube has an earthing terminal (C);

2°) A rectangular strip of steel plate, height 29 2/4", width 5" and thickness 1/4", with rounded corners and the bottom edge curving slightly away from the wall. The plate is welded to the support tube and the bracket and is provided with four holes (I - diam. 2/4"), for fixing to the wall with expansion bolts. The power cable enters the wall bracket through the rear hole (A) on the plate or through a slot.

The total height of the wall bracket is 29 2/4", with an effective projection of 29 1/4".The total height of the wall bracket is 29 2/4" with an effective projection of 29 1/4".

Protection of surfaces

Please refer to the specification on painting procedures of the materials.

