

Project location:			
Project name:			
Model #:	4108.181	Date	

DESCRIPTION

Description

The top section is made in UNI EN 1561 cast iron, and corresponds in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The top section is composed as follows:

1°) A cast iron element height 13 1/4" with a circular base (diam. 9 3/4") surmounted by a fillet and a junction. The central section is in the form of a cube (length of sides 4"), with a joint on one face for attaching the bracket. The three other faces are decorated with rosettes, one of which, opposite the joint, is detachable (D). Above the central section is a sphere (diam. 4") decorated in the lower part with four leaves. The element is fixed to the column (B) with three M10 stainless steel bolts (C), and rotation is prevented by a bolt (H) screwed into a slot in the core (A).

2°) A bracket protruding 23 2/4", height 22 3/4", with a curve radius of 14 1/4". The bracket is decorated with eight flutes along the curved section (thickness 1 3/4") and a cube at the end, which is in turn decorated with rosettes on two faces. The bracket is attached to the first element with four M8 stainless steel bolts (E). At the upper end the bracket has a 3/4" GAS threaded sleeve (F) with stainless steel nut and rose for attaching the light fixture. Inside the bracket is a tube for the passage of a power cable of diameter 2/4".


The assembled bracket protrudes for 23 2/4" to the light fixture attachment.

The total height is 25 2/4".


Protection of surfaces

Please refer to the specification on painting procedures of the materials.


DRAWINGS



Section



Exploded



Prospect