

Project location:			
Project name:			
Model #:	2151.002.018	Date	

Description

Fixed bench in UNI EN 1561 cast iron and iroko wood (or equivalent) brown colour, corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The bench is composed as follows:


- 1°) Two cast iron support elements, height 31 1/4", depth 28 3/4". Each element has a base that is 22 2/4" long and is fitted with two lugs (A) for cementing into the ground, height 2", depth 1 2/4", with a distance between centres of 18 2/4", and with junctions for the wooden planks of the seat and backrest. Ornamentation is composed of branches, leaves, volutes and a large flower in the middle (B), from which a fruit motif diverges. Ornamentation also continues up the backrest support.
- 2°) A seat, depth 15", composed of six slats of solid seasoned iroko wood (or equivalent), length 5' 10 3/4", width 1 2/4" and thickness 1 2/4". Each slat is fixed to the support legs with four M6 stainless steel bolts.
- 3°) A backrest, height 13", composed of two planks and one slat of solid seasoned iroko wood (or equivalent), length 5' 10 3/4" and thickness 1 2/4". The two planks are each 4 3/4" wide, and the central slat is 1 2/4" wide. The two planks and the slat are fixed to the support legs with a total of twenty M6 stainless steel bolts.

The assembled bench has the following dimensions:


total height 32 1/4" – total length 5' 10 3/4" – total depth 28 3/4" – distance between centres of supports 4' 4 3/4" – seat height 15 3/4" – seat depth 15" – backrest height 32 1/4" – angle between seat and backrest 109°.

Protection of surfaces


Please refer to the specification on painting procedures of the materials.



Front view



Side - Left/Right supports



Exploded view