

Project location:			
Project name:			
Model #:	4215.109.001	Date	

Description

Wall bracket in FE 360 UNI EN 10219-1 steel electrolytically cold-galvanized to UNI ISO 2081 standards, corresponding in shape, size and ornamentation to the diagrams, which are an integral part of the specifications.

The wall bracket is composed as follows:

1°) A steel support tube (diam. 1 1/4", length 3' 5 1/4"). At the outer extremity the tube has a junction (C) for attaching the suspended light fixture, consisting in a bush that is tapered externally and is welded to the support tube. Internally, this bush has a 3/4" GAS thread for attaching the light fixture, and an M6 safety screw is also provided (F). The junction is surmounted by an element (D) decorated with a torus, a moulding and a sphere. The support tube has a slot (B) for leading a 2/4" diameter power cable into the interior, and an earthing terminal (A).

2°) A steel bracket (section 1 1/4" x 2/4") projecting 29 1/4". The bracket, support tube and the two steel collars (E) are welded together. The ornamentation of the bracket consists in two spirals (a, b) with heights of 11 2/4" and 6 1/4".

3°) A rectangular strip of steel plate, height 17 3/4", width 4" and thickness 1/4", with rounded corners and the bottom edge curving slightly away from the wall. The plate is welded to the support tube and the bracket and is provided with three holes (diam. 2/4"), two at the top and one at the bottom, for fixing to the wall with expansion bolts.

The total height of the wall bracket is 17 3/4", with an effective projection of 3' 5 1/4".

Protection of surfaces

Please refer to the specification on painting procedures of the materials.

